

Tempo 2 RVP251

RVP251 MHN-TD150W/842 IC A

MHN-TD, 150 W, Asymmetrical

Tempo is a complete floodlighting range offering a wide choice of lamp types and symmetrical and asymmetrical reflectors. It is designed for general-purpose floodlighting, and is particularly suited to small- to medium-scale area or surface lighting. The Tempo series' compact housing guarantees optimum visual integration. Anodized-aluminum reflectors ensure a highly efficient beam distribution, while the nylon bolt caps feature a goniometric aiming device for easy adjustment and alignment. A universal mounting bracket allows ceiling, wall or surface mounting with a wide range of adjustment for both down- and uplighting. Tempo's all-weather construction is designed to make cleaning and servicing easy and fast. Access to the lamp and gear is simple, via the hinged front glass with its quick-release stainless-steel clips. All Tempo luminaires are RoHS-compliant.

Product data

General Information	
Lamp family code	MHN-TD
Gear	CONV [Conventional]
CE mark	Yes
ENEC mark	-
Warranty period	1 years
EU RoHS compliant	Yes
Light Technical	
Upward light output ratio	0
Correlated Color Temperature (Nom)	4200 K
Color rendering index (CRI)	85
Number of light sources	1
Light source color	842 neutral white

Optical cover type	Flat glass
Optic type outdoor	Asymmetrical
Operating and Electrical	
Input Voltage	230 V
Line Frequency	50 Hz
Initial CLO power consumption	{NO} - W
End CLO power consumption	{NO} - W
Power Consumption	150 W
Power Factor (Fraction)	0.85
Connection	Screw connection block 3-pole
Cable	-

Datasheet, 2023, October 25 data subject to change


Tempo 2 RVP251

Temperature		
Ambient temperature range	-25 to +35 °C	
Controls and Dimming		
Dimmable	No	
Constant light output	No	
Mechanical and Housing		
Housing Material	Aluminum die cast	
Reflector material	Aluminum	
Optic material	Aluminum	
Optical cover material	Glass	
Fixation material	Steel	
Housing Color	Grey	
Optical cover shape	Flat	
Optical cover finish	Clear	
Overall length	346 mm	
Overall width	363 mm	
Overall height	118 mm	
Effective projected area	0.123 m²	

Dimensions (Height x Width x Depth)	118 x 363 x 346 mm
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Protection class IEC	Safety class I
Product Data	
Order product name	RVP251 MHN-TD150W/842 IC A
Full product name	RVP251 MHN-TD150W/842 IC A
Full product code	871155914960800
Order code	910502547418
Material Nr. (12NC)	910502547418
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711559149608
Numerator - Packs per outer box	1
EAN/UPC - Case	8711559149608

Dimensional drawing







© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.