


Tempo 3 RVP351

RVP351 SON-TPP250W K IC S

250 W, Symmetrical

Tempo is a complete floodlighting range offering a wide choice of lamp types and symmetrical and asymmetrical reflectors. It is ideally suited to a variety of outdoor applications – from architectural, facade and billboard lighting to area and (recreational) sports lighting. Besides the Tempo 1, 2 and 3 versions, the range features the high-power Tempo 4, which is available with a variety of light sources up to 2000 W and features an external gear unit. Designed for medium to large-scale floodlighting of sports facilities and similar areas, it is available in single or double-lamp versions and with a choice of narrow or wide-beam optics. The Tempo series' compact housing guarantees optimum visual integration. Anodized-aluminum reflectors ensure a highly efficient beam distribution, while the nylon bolt caps feature a goniometric aiming device for easy adjustment and alignment. Access to the lamp and gear is quick and easy, via the hinged front glass with its quick-release stainless-steel clips. All Tempo luminaires are RoHS-compliant.

Product data

General Information	
Lamp family code	SON-TPP [SON-T PIA Plus]
Gear	CONV [Conventional]
CE mark	Yes
Warranty period	1 years
ENEC mark	-
Glow-wire test	Temperature 850 °C, duration 5 s
EU RoHS compliant	Yes

Light Technical	
Upwards light output ratio	0
Correlated Colour Temperature	2000 K
Colour rendering index (CRI)	25
Light source colour	220 gold
Optical cover type	Flat glass
Optic type outdoor	Symmetrical

Operating and Electrical	
Input Voltage	230 V
Line Frequency	50 Hz
Initial CLO power consumption	{NO} - W
End CLO power consumption	{NO} - W
Power Consumption	250 W
Power Factor (Fraction)	0.85

Tempo 3 RVP351

Connection	Screw connection block 3-pole
Cable	-

Effective projected area	0.165 m²
Dimensions (height x width x depth)	146 x 464 x 428 mm

Temperature	
Ambient temperature range	-25 to +35 °C


Controls and Dimming	
Dimmable	No
Constant light output	No

Mechanical and Housing	
Housing material	Aluminium die cast
Reflector material	Aluminium
Optic material	Aluminium
Optical cover/lens material	Glass
Fixation material	Steel
Housing Colour	Grey
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	428 mm
Overall width	464 mm
Overall height	146 mm

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Protection class IEC	Safety class I

Product Data	
Order product name	RVP351 SON-TPP250W K IC S
Full product name	RVP351 SON-TPP250W K IC S
Full EOC	871155914975200
Order code	14975200
Material no. (12 NC)	910502548918
Local order code	RVP351S250SK
SAP numerator – quantity per pack	1
EAN/UPC — Product/Case	8711559149752
Numerator – packs per outer box	1
EAN/UPC - Case	8711559149752

Dimensional drawing



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.