



ParkView LED

BPS965 GRN30/830 II GR CLO-DDF6 60P C4K

Parkview LED, LED GreenLine 3000 lm, Constant light output and DynaDimmer fixed presets version 6, Post-top for diameter 60 mm

For urban settings, customers want a luminaire that combines unobtrusive elegance with operational efficiency. ParkView LED's unique construction of clear polycarbonate and white lamellas gives the luminaire a sense of lightness and minimalism. Its cone-shaped bowl marked in quarters, cone-shaped louver and base ensure a smooth transition to the pole. ParkView LED provides a symmetrical light distribution, and the vertical lamellas which direct the light towards the ground also cut spill light and minimize glare as they shield the light source. Design: Tegnestuen Bjarne Frost, Denmark

Product data

General Information	
Lamp family code	GRN30 [LED GreenLine 3000 lm]
Light source replaceable	Yes
Driver included	Yes
Product family code	BPS965 [Parkview LED]
Lighting Technology	LED
CE mark	Yes
Embedded control	Constant light output and DynaDimmer fixed
	presets version 6
	presets version o
	presets version o
Light Technical	presens version o
Light Technical Luminous Flux	3,000 lm
	3,000 lm
Luminous Flux	3,000 lm

Color rendering index (CRI)	83
Number of light sources	1
Light source color	830 warm white
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Power Consumption	31 W
Cable	Cable 4.0 m without plug
Temperature	
Ambient temperature range	−30 to +25 °C

Datasheet, 2023, September 4 data subject to change

ParkView LED

Controls and Dimming	
Dimmable	Yes
Driver/power unit/transformer	Power supply unit regulating
Control interface	-
Constant light output	Yes
Mechanical and Housing	
Housing Material	Aluminum
Housing Color	Grey
Mounting device	Post-top for diameter 60 mm
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)		
Init. Color Rendering Index Tolerance +/-2		
Product Data		
Order product name	BPS965 GRN30/830 II GR CLO-DDF6 60P C4K	
Full product name	BPS965 GRN30/830 II GR CLO-DDF6 60P C4K	
Full product code	871829108474700	
Order code	910502610430	
Material Nr. (12NC)	910502610430	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8718291084747	
Numerator - Packs per outer box	1	
EAN/UPC - Case	8718291084747	

Dimensional drawing





