



TBS165

TBS165 G 4xTL5-14W/840 HFS M2 PIP SC

4, TL5, 14 W, 840 neutral white, HF Standard, Matt mirror ribbed lamellae louver, Push-in connector and pull relief

Designed to address the need for energy-efficient basic lighting, the TBS165 luminaire makes it possible to save energy by replacing outdated electromagnetic installations with Philips TL5 technology. Featuring innovative dedicated TL5 optics, a choice of ballasts, sensors (presence detection, daylight regulation) and emergency lighting, the TBS165 range can be used for general lighting in a wide variety of applications, including offices, corridors, schools and shops (supermarkets, DIY). Combining high-frequency gear, sensors and MASTER TL5 lamps, it allows substantial energy savings. The low-height recessed luminaire fits in exposed ceilings. Conveniently, it does not have to be opened, as it has pre-installed lamps and can be connected from the outside.

Product data

| General Information | | Operating and Electrical | |
|-------------------------|---|-------------------------------|-----------------------------------|
| Lamp family code | TL5 [TL5] | Input Voltage | 220 to 240 V |
| Gear | HFS [HF Standard] | Power Consumption | 14 W |
| CE mark | Yes | Connection | Push-in connector and pull relief |
| Flammability mark | For mounting on normally flammable surfaces | Approval and Application | |
| Glow-wire test | Temperature 850 °C, duration 5 s | Ingress protection code | IP20 [Finger-protected] |
| Light Technical | | Mech. impact protection code | IK02 [0.2 J standard] |
| Number of light sources | 4 | Protection class IEC | Safety class I |
| Light source color | 840 neutral white | Application Conditions | |
| Optic type | Matt mirror ribbed lamellae louver | Suitable for random switching | Not applicable |

TBS165

| Product Data | |
|---------------------|--------------------------------------|
| Order product name | TBS165 G 4xTL5-14W/840 HFS M2 PIP SC |
| Full product name | TBS165 G 4xTL5-14W/840 HFS M2 PIP SC |
| Full product code | 871794388800900 |
| Order code | 88800900 |
| Material Nr. (12NC) | 910503651618 |

| | |
|---------------------------------|---------------|
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8717943888009 |
| Numerator - Packs per outer box | 1 |
| EAN/UPC - Case | 8717943888009 |

Dimensional drawing

