PHILIPS Lighting



AmphiLux, recessed

BBC400 1xLED-HB/BL 12V 10

1 pc - LED High Brightness - Narrow beam angle 10°

People want to spend more quality time outdoors with family and friends. The AmphiLux recessed spotlight range is designed to enhance outdoor social areas (gardens, terraces, fountains, waterfalls, etc.) with architectural lighting.;AmphiLux is a family of LED spots featuring a stunning, sleek Italian design with a stylish chrome finish. These solutions can be used under water and in semi-wet and dry environments. Available in Micro, Mini and Compact sizes, the range offers a choice of dynamic white-light and colored-light versions for maximum flexibility in tasteful flood and accent lighting.

Product data

| General Information | |
|-------------------------------|---|
| Number of light sources | 1 рс |
| Lamp family code | LED-HB [LED High Brightness] |
| Light source color | Blue |
| Light source replaceable | No |
| Driver/power unit/transformer | - |
| Driver included | No |
| Optical cover/lens type | - |
| Protection class IEC | Safety class III |
| CE mark | CE mark |
| Lifetime to 50% luminous flux | 200000 h |
| Lifetime to 70% luminous flux | 147000 h |
| Lifetime to 90% luminous flux | 43000 h |
| Optic type outdoor | Narrow beam angle 10° |
| Serviceability class | Class C, luminaire without serviceable parts, not |
| | serviceable |
| | |

| Operating and Electrical | | |
|---|---|--|
| | | |
| Input Voltage | 12 V | |
| | | |
| Controls and Dimming | | |
| Dimmable | No | |
| | | |
| Approval and Application | | |
| Ingress protection code | IP68 [Dust penetration-protected, pressure | |
| | watertight] | |
| Mech. impact protection code | IK10 [20 J vandal-resistant] | |
| | | |
| Initial Performance (IEC Compliant) | | |
| Initial luminous flux (system flux) 14 lm | | |
| Initial LED luminaire efficacy | 9 lm/W | |
| Initial input power | 1.5 W | |
| | | |


AmphiLux, recessed

| Application Conditions | |
|---------------------------|---------------------------|
| Ambient temperature range | -20 to +35 ℃ |
| | |
| Product Data | |
| Full product code | 871794389328799 |
| Order product name | BBC400 1xLED-HB/BL 12V 10 |
| EAN/UPC - Product | 8717943893287 |
| Order code | 910503674418 |

| Numerator - Quantity Per Pack | 1 |
|---------------------------------|--------------|
| Numerator - Packs per outer box | x 6 |
| Material Nr. (12NC) | 910503674418 |
| Net Weight (Piece) | 0.335 kg |
| | |



Dimensional drawing





© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, August 5 - data subject to change