



AmphiLux, surface mounted

BVD420 12xLED-HB-2700-6000 E 30

12 pcs - LED High Brightness - Empty, without gear - Medium beam angle 30°

People want to spend more quality time outdoors with family and friends. The AmphiLux surface-mounted spotlight range is designed to enhance outdoor social areas (gardens, terraces, fountains, waterfalls, etc.) with architectural lighting. AmphiLux is a family of LED spots featuring a stunning, sleek Italian design with a stylish chrome finish. These solutions can be used under water and in semi-wet and dry environments. Available in Micro, Mini and Compact sizes, the range offers a choice of dynamic white-light and colored-light versions for maximum flexibility in tasteful flood and accent lighting.

Product data

General Information		Optic type outdoor	
Number of light sources	12 pcs	Medium beam angle 30°	
Lamp family code	LED-HB [LED High Brightness]	Serviceability class	
Light source replaceable	No	Class C, luminaire without serviceable parts, not serviceable	
Gear	E [Empty, without gear]	Operating and Electrical	
Driver/power unit/transformer	-	Input Voltage	
Driver included	No	12 V	
Optical cover/lens type	-	Controls and Dimming	
Protection class IEC	Safety class III	Dimmable	
CE mark	CE mark	Yes	
Lifetime to 50% luminous flux	200000 h	Approval and Application	
Lifetime to 70% luminous flux	147000 h	Ingress protection code	
Lifetime to 90% luminous flux	43000 h	IP68 [Dust penetration-protected, pressure watertight]	

AmphiLux, surface mounted

Mech. impact protection code IK05 [0.7 J]

Initial Performance (IEC Compliant)

Initial luminous flux (system flux) 700 lm

Initial LED luminaire efficacy 58 lm/W

Init. Corr. Color Temperature 2700 to 6000 K

Init. Color Rendering Index 80

Initial input power 12 W

Application Conditions

Ambient temperature range -20 to +35 °C

Product Data

Full product code 871794389498799

Order product name BVD420 12xLED-HB-2700-6000 E 30

EAN/UPC - Product 8717943894987


Order code 910503685918

Numerator - Quantity Per Pack 1


Numerator - Packs per outer box 4

Material Nr. (12NC) 910503685918

Net Weight (Piece) 3.735 kg



Dimensional drawing



AmphiLux BBD/BVD400

