

eW Cove MX Powercore

eW Cove MX Powercore, 2700 K, 50° x 70° Beam Angle, 12.5 W/ft, 305 mm (1 ft)

eW Cove MX Powercore, 2700 K, 50° x 70° Beam Angle, 12.5 W/ft, 305 mm (1 ft)

With its superior light output, wide beam angle, and range of fixed colors and color temperatures, eW Cove MX Powercore can be used for accent lighting and indirect general illumination, as well as the full range of wall and ceiling cove applications. This fixture meets or exceeds the performance of comparable linear fluorescent strip cove lights while lowering installation, energy, and maintenance costs. eW Cove MX Powercore offers environmentally conscious buyers a green, energy-efficient lighting solution without sacrificing quality or quantity of light.;Integrated Powercore technology ensures rapid, efficient and accurate control of power output to the fixture directly from line voltage, eliminating the need for external power supplies. Use of standard wiring dramatically simplifies installation and helps lower total system cost.

Product data

General information	
Number of light sources	10 [10 pcs]
Lamp family code	LED-HB [LED High Brightness]
Light source color	Warm white
Light source replaceable	No
Driver/power unit/transformer	PSR [Power supply unit regulating]
Driver included	Yes
Optic type	MB [Medium beam]
Optical cover/lens type	PC [Polycarbonate bowl/cover]

Luminaire light beam spread	50° x 70°
Protection class IEC	Safety class I (I)
Ready-to-install	Ready-to-install
Type description	No
CE mark	CE mark
UL mark	UL and cUL mark
CCC mark	CCC mark

eW Cove MX Powercore

Operating and electrical	
Input Voltage	100 to 277 V
Input Frequency	50 to 60 Hz

Controls and dimming	
Dimmable	Yes

Mechanical and housing	
Housing Material	Aluminum die–cast
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Length	305 mm
Color	White

Approval and application	
Ingress protection code	IP20 [Finger-protected]
FCC mark	FCC Class B


Initial performance (IEC compliant)	
Initial luminous flux (system flux)	384 lm
Initial luminous flux at color temperature of 2700 K	384 lm
Initial LED luminaire efficacy	34.9 lm/W
Init. Corr. Color Temperature	2700 K
Init. Color Rendering Index	83
Initial input power	12.5 W

Over time performance (IEC compliant)	
Lumen Maintenance 50% at 25°C Calculated	100000
Lumen Maintenance 50% at 25°C Reported	65000
Lumen Maintenance 50% at 50°C Calculated	100000
Lumen Maintenance 50% at 50°C Reported	65000
Lumen Maintenance 70% at 25°C Calculated	100000
Lumen Maintenance 70% at 25°C Reported	65000
Lumen Maintenance 70% at 50°C Calculated	100000
Lumen Maintenance 70% at 50°C Reported	65000

Application conditions	
Ambient temperature range	-20 to +50 °C
Maximum dim level	10% (depends on dimmer, ELV)
Suitable for random switching	Yes

Product data	
Full product code	871794379650299
Order product name	BCX416 10xLED-HB-2700 100-277V MB
EAN/UPC - Product	8717943796502
Order code	523-000050-01
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	20
Material Nr. (12NC)	910503700979
Net Weight (Piece)	0.460 kg
Commercial Code	523-000050-01
Commercial Code	eW Cove MX Powercore, 2700 K, 50° x 70° Beam Angle, 12.5 W/ft, 305 mm (1 ft)

Dimensional drawing



BCX416 10xLED-HB-2700 100-277V MB

eW Cove MX Powercore

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com
2022, September 15 - data subject to change