



iW Burst Compact Powercore

iW Burst Compact Powercore, 10° x 41° Spread Lens, Black Housing, UL/cUL/CE, Architectural

iW Burst Compact Powercore, 10° x 41° Spread Lens, Black Housing, UL/cUL/CE, Architectural

iW Burst Compact Powercore is a high-output, exterior-rated LED spotlight designed for accent and site lighting. It combines channels of warm and cool LEDs to offer variable colour temperatures ranging from warm to cool. Standard and compact format Architectural and Landscape versions support a range of uplighting, floodlighting, and decorative lighting applications. Integrated Powercore technology ensures rapid, efficient and accurate control of power output to the fixture directly from line voltage, eliminating the need for external power supplies. Use of standard wiring dramatically simplifies installation and helps lower total system cost.

Product data

General Information		Lifetime	
Number of light sources	12 [12 pcs]	Lifetime to 50% luminous flux	50000 h
Lamp family code	LED-HB [LED High Brightness]	Lifetime to 70% luminous flux	50000 h
Lamp colour code	Cool white and warm white	Operating and Electrical	
Light source replaceable	No	Input Voltage	100 to 240 V
Driver included	No	Input frequency	50 to 60 Hz
Optical cover/lens type	GT [Tempered glass]	Controls and Dimming	
Luminaire light beam spread	8°	Dimmable	Yes
Protection class IEC	Safety class I (I)		
CE mark	CE mark		
UL mark	UL and cUL mark		

iW Burst Compact Powercore

Mechanical and Housing

Housing configuration	BV [Basic version]
Colour	Black

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Vibration standard	Complies with ANSI C136.31, 3G
Vibration rating	Complies with ANSI C136.31, 3G

Initial Performance (IEC Compliant)

Initial input power	17.5 W
---------------------	--------

Over Time Performance (IEC Compliant)

Lumen Maintenance 50% at 25 °C Reported	50000
Lumen Maintenance 50% at 50 °C Reported	50000
Lumen Maintenance 70% at 25 °C Reported	50000


Lumen Maintenance 70% at 50 °C Reported	35000
--	-------

Product Data

Full product code	871794379292499
Order product name	BCP464 12xLED-HB-2700-6500 BK ULCE
EAN/UPC – product	8717943792924
Order code	523-000067-04
SAP numerator – quantity per pack	1
Numerator – packs per outer box	4
SAP material	910503702209
SAP net weight (piece)	3.500 kg
Commercial Code	523-000067-04
Commercial Code	iW Burst Compact Powercore, 10° x 41° Spread Lens, Black Housing, UL/cUL/CE, Architectural



Dimensional drawing



iW Burst Compact Powercore

