



ColorGraz QLX Powercore

ColorGraz QLX Powercore, RGB, 10° x 60° Beam Angle, 610 mm (2 ft)

ColorGraz QLX Powercore, RGB, 10° x 60° Beam Angle, 610 mm (2 ft)

Many architectural structures need a linear fixture capable of illuminating several storeys with minimal setback and reduced power consumption. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasise their brands. Graze QLX Powercore is capable of illuminating over 10 metres at very close setback distances. Powercore technology enables simple installation and long product run lengths.

Product data


General Information	
Lamp family code	LED-HB [LED High Brightness]
Light source colour	RGB
Light source replaceable	No
Driver included	Yes
Luminaire light beam spread	10° x 60°
Protection class IEC	Safety class I
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 70% luminous flux	100000 h
Operating and Electrical	
Input Voltage	100 to 277 V

Input frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Extruded aluminium
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Length	609 mm
Colour	aluminium

ColorGraz e QLX Powercore

Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Vibration standard	Complies with ANSI C136.31, 3G
Vibration rating	Complies with ANSI C136.31, 3G
Initial Performance (IEC Compliant)	
Initial input power	30 W
Over Time Performance (IEC Compliant)	
Lumen Maintenance 50% at 25 °C Calculated	100000
Lumen Maintenance 50% at 25 °C Reported	100000
Lumen Maintenance 50% at 50 °C Calculated	80000
Lumen Maintenance 50% at 50 °C Reported	80000
Lumen Maintenance 70% at 25 °C Calculated	60000
Lumen Maintenance 70% at 25 °C Reported	100000
Lumen Maintenance 70% at 50 °C Calculated	60000
Lumen Maintenance 70% at 50 °C Reported	91000

Dimensional drawing



Application Conditions	
Ambient temperature range	-40 to +50 °C
Product Data	
Full product code	871829160409999
Order product name	BCS467 10x60 RGB L609
EAN/UPC – product	8718291604099
Order code	123-000079-26
SAP numerator – quantity per pack	1
Numerator – packs per outer box	4
SAP material	910503703353
SAP net weight (piece)	2.700 kg
Commercial Code	123-000079-26
Catalogue number description	ColorGraz e QLX Powercore, RGB, 10° x 60° Beam Angle, 610 mm (2 ft)

