



# eColor Graze MX Powercore

**eColor Graze MX Powercore, Blue, 10° x 60° Beam Angle, 305 mm (1 ft)**

Blue - 10° x 60° - 305 mm - Aluminum

Many architectural structures need a linear fixture capable of illuminating multiple storeys with minimal setback. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasize their brands. Graze MX Powercore is capable of illuminating over 20 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

## Product data

General Information		Controls and Dimming	
Lamp family code	LED-HB [ LED High Brightness]	Dimmable	Yes
Light source colour	Blue		
Light source replaceable	No		
Driver included	Yes		
Optical cover/lens type	PCC [ Polycarbonate bowl/cover clear]		
Luminaire light beam spread	10° x 60°		
Protection class IEC	Safety class I (I)		
CE mark	CE mark		
UL mark	UL and cUL mark		
Operating and Electrical		Mechanical and Housing	
Input Voltage	100 to 277 V	Housing material	Aluminum extruded
Input frequency	50 to 60 Hz	Optic material	Polycarbonate
		Optical cover/lens material	Polycarbonate
		Length	305 mm
		Colour	Aluminum
		Approval and Application	
		Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
		Mech. impact protection code	IK10 [ 20 J vandal-resistant]
		Vibration standard	Complies with ANSI C136.31, 3G

eColor Graze MX Powercore

Vibration rating	Complies with ANSI C136.31, 3G
Initial Performance (IEC Compliant)	
Initial input power	15 W
Application Conditions	
Ambient temperature range	-40 to +50 °C
Product Data	
Full product code	871829160523299
Order product name	BCS439 10x60 BL L305
EAN/UPC – product	8718291605232

Order code	223-000080-06
SAP numerator – quantity per pack 1	
Numerator – packs per outer box	4
SAP material	910503703395
Net Weight (Piece)	1.200 kg
Commercial Code	223-000080-06
Commercial Code	eColor Graze MX Powercore, Blue, 10° x 60° Beam Angle, 305 mm (1 ft)



Dimensional drawing

