



## iW Graze QLX Powercore

## iW Graze QLX Powercore, 10° x 60° Beam Angle, 914 mm (3 ft)

iW Graze QLX Powercore, 10° x 60° Beam Angle, 914 mm (3 ft)

Many architectural structures need a linear fixture capable of illuminating several storeys with minimal setback and reduced power consumption. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasize their brands. Graze QLX Powercore is capable of illuminating over 10 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

## **Product data**

General Information	
Lamp family code	LED-HB [ LED High Brightness]
Light source replaceable	No
Driver included	Yes
Luminaire light beam spread	10° x 60°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL mark
Lifetime to 70% luminous flux	100000 h
Operating and Electrical	
Input Voltage	100 to 277 V
Input frequency	50 to 60 Hz


Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Length	914 mm
Approval and Application	
Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [ 20 J vandal-resistant]
Vibration standard	Not compliant to ANSI C136.31, 3G. Special orders
	are available to conform to the standard. Please
	contact your Color Kinetics Lighting Sales rep for
	custom configurations.
Vibration rating	Not compliant to ANSI C136.31, 3G. Special orders
	are available to conform to the standard. Please

## iW Graze QLX Powercore

contact your Color Kinetics Lighting Sales rep for		
custom configurations.		
Initial Performance (IEC Compliant)		
45 W		
-20 to +50 °C		
871829160958200		
BCS437 10x60/2700-6500 L914		

EAN/UPC – product	8718291609582	
Order code	523-000079-31	
SAP numerator – quantity per pack 1		
Numerator – packs per outer box	1	
SAP material	910503703675	
SAP net weight (piece)	3.800 kg	
Commercial Code	523-000079-31	
Catalogue number description	iW Graze QLX Powercore, 10° x 60° Beam Angle, 914	
	mm (3 ft)	







© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2021, May 13 - data subject to change