



# eW Graze MX Powercore

## BCS419 60x30/5500 L609

eW Graze MX Powercore, 5500 K,  $60^{\circ}$  x  $30^{\circ}$  Beam Angle, 610 mm (2 ft)

Many architectural structures need a linear fixture capable of illuminating multiple storeys with minimal setback. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasize their brands. Graze MX Powercore is capable of illuminating over 20 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

#### **Product data**

| General Information           |                               |
|-------------------------------|-------------------------------|
| Lamp family code              | LED-HB [ LED High Brightness] |
| Light source colour           | Neutral white                 |
| Light source replaceable      | No                            |
| Driver included               | Yes                           |
| Luminaire light beam spread   | 60° x 30°                     |
| Protection class IEC          | Safety class I (I)            |
| CE mark                       | CE mark                       |
| UL mark                       | UL and cUL mark               |
| Lifetime to 50% luminous flux | 60000 h                       |
| Lifetime to 70% luminous flux | 60000 h                       |
|                               |                               |
| Operating and Electrical      |                               |
| Input Voltage                 | 100 to 277 V                  |
|                               |                               |

| Input frequency              | 50 to 60 Hz                             |
|------------------------------|---|
|                              |   |
| Controls and Dimming         |   |
| Dimmable                     | Yes                                     |
|                              |   |
| Mechanical and Housing       |   |
| Housing material             | Aluminum extruded                       |
| Optical cover/lens material  | Polycarbonate                           |
| Length                       | 609 mm                                  |
|                              |   |
| Approval and Application     |   |
| Ingress protection code      | IP66 [ Dust penetration-protected, jet- |
|                              | proof]                                  |
| Mech. impact protection code | IK10 [ 20 J vandal-resistant]           |
| Vibration standard           | Complies with ANSI C136.31, 3G          |
|                              |   |

Datasheet, 2022, February 21 data subject to change


## **eW Graze MX Powercore**

| libration rating                       | Complies with ANSI C136.31, 3G |  |
|--|--------------------------------|--|
|  |                                |  |
| nitial Performance (IEC Compliant)     |                                |  |
| nit. Corr. Colour Temperature          | 5500 K                         |  |
| nitial input power                     | 28 W                           |  |
|  |                                |  |
| Over Time Performance (IEC Compliant)  |                                |  |
| umen Maintenance 50% at 25 °C Reported | 60000                          |  |
| umen Maintenance 50% at 50 °C Reported | 60000                          |  |
| umen Maintenance 70% at 25 °C Reported | 60000                          |  |
| umen Maintenance 70% at 50 °C Reported | 60000                          |  |
|  |                                |  |
| Application Conditions                 |                                |  |
| Ambient temperature range              | -20 to +50 °C                  |  |

| Product Data                      |  |
|-----------------------------------|--|
| Full product code                 | 871829161042799                          |
| Order product name                | BCS419 60x30/5500 L609                   |
| EAN/UPC – product                 | 8718291610427                            |
| Order code                        | 523-000080-29                            |
| SAP numerator – quantity per pack | 1  |
| Numerator – packs per outer box   | 4  |
| SAP material                      | 910503703717                             |
| SAP net weight (piece)            | 2.700 kg                                 |
| Commercial Code                   | 523-000080-29                            |
| Catalogue number description      | eW Graze MX Powercore, 5500 K, 60° x 30° |
|                                   | Beam Angle, 610 mm (2 ft)                |
| -                                 | ·  |



### Dimensional drawing



BCS419 60x30/5500 L609



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.