



# eW Graze QLX Powercore

# BCS427 15x30/5500 L305

eW Graze QLX Powercore, 5500 K,  $15^{\circ}$  x  $30^{\circ}$  Beam Angle, 305 mm (1 ft)

Many architectural structures need a linear fixture capable of illuminating several storeys with minimal setback and reduced power consumption. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasize their brands. Graze QLX Powercore is capable of illuminating over 10 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

### **Product data**

General Information	
Lamp family code	LED-HB [ LED High Brightness]
Light source colour	Cool white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	PCC [ Polycarbonate bowl/cover clear]
Luminaire light beam spread	15° x 30°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 70% luminous flux	100000 h
Operating and Electrical	
Input Voltage	100 to 277 V

Input frequency	50 to 60 Hz
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing material	Aluminum extruded
Optical cover/lens material	Polycarbonate
Length	305 mm
Colour	Aluminum
Approval and Application	
Ingress protection code	IP66 [ Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK10 [ 20 J vandal-resistant]

Datasheet, 2022, February 21 data subject to change

# eW Graze QLX Powercore

Vibration standard	Complies with ANSI C136.31, 3G	
Vibration rating	Complies with ANSI C136.31, 3G	
Initial Performance (IEC Compliant)		
Init. Corr. Colour Temperature	4000 K	
Initial input power	15 W	
Over Time Performance (IEC Compliant)		
Lumen Maintenance 50% at 25 °C Reported 60000		
Lumen Maintenance 50% at 50 °C Reported 60000		
Lumen Maintenance 70% at 25 °C Reported 60000		
Lumen Maintenance 70% at 50 °C Reported 60000		
Application Conditions		


-40 to +50 ℃

Product Data	
Full product code	871829161111099
Order product name	BCS427 15x30/5500 L305
EAN/UPC – product	8718291611110
Order code	523-000081-08
SAP numerator – quantity per pack	1
Numerator – packs per outer box	4
SAP material	910503703755
SAP net weight (piece)	1.200 kg
Commercial Code	523-000081-08
Catalogue number description	eW Graze QLX Powercore, 5500 K, 15° x 30°
	Beam Angle, 305 mm (1 ft)



## Dimensional drawing

Ambient temperature range



BCS427 15x30/5500 L305



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.