



eW Graze QLX Powercore

eW Graze QLX Powercore, 2700 K, 60° x 30° Beam Angle, 610 mm (2 ft)

eW Graze QLX Powercore, 2700 K, 60° x 30° Beam Angle, 610 mm (2 ft)

Many architectural structures need a linear fixture capable of illuminating several storeys with minimal setback and reduced power consumption. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasize their brands. Graze QLX Powercore is capable of illuminating over 10 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

Product data

| General information | |
|-------------------------------|---------------------------------------|
| Lamp family code | LED-HB [LED High Brightness] |
| Light source colour | Warm white |
| Light source replaceable | No |
| Driver included | Yes |
| Optical cover/lens type | PCC [Polycarbonate bowl/cover clear] |
| Luminaire light beam spread | 60° x 30° |
| Protection class IEC | Safety class I (I) |
| CE mark | CE mark |
| UL mark | UL and cUL mark |
| Lifetime to 70% luminous flux | 100000 h |

| Operating and electrical | |
|-----------------------------|-------------------|
| Input Voltage | 100 to 277 V |
| Input frequency | 50 to 60 Hz |
| Controls and dimming | |
| Dimmable | Yes |
| Mechanical and housing | |
| Housing material | Aluminum extruded |
| Optical cover/lens material | Polycarbonate |
| Length | 609 mm |
| Colour | Aluminum |

eW Graze QLX Powercore

| | |
|---|---|
| Approval and application | |
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK10 [20 J vandal-resistant] |
| Vibration standard | Complies with ANSI C136.31, 3G |
| Vibration rating | Complies with ANSI C136.31, 3G |
| Initial performance (IEC compliant) | |
| Init. Corr. Colour Temperature | 2700 K |
| Initial input power | 28 W |
| Over time performance (IEC compliant) | |
| Lumen Maintenance 50% at 25 °C Reported | 60000 |
| Lumen Maintenance 50% at 50 °C Reported | 60000 |
| Lumen Maintenance 70% at 25 °C Reported | 60000 |
| Lumen Maintenance 70% at 50 °C Reported | 60000 |
| Application conditions | |
| Ambient temperature range | -40 to +50 °C |

| | |
|-----------------------------------|---|
| Product data | |
| Full product code | 871829161130199 |
| Order product name | BCS427 60x30/2700 L609 |
| EAN/UPC – product | 8718291611301 |
| Order code | 523-000081-27 |
| SAP numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 4 |
| SAP material | 910503703774 |
| Net Weight (Piece) | 2.700 kg |
| Commercial Code | 523-000081-27 |
| Catalogue number description | eW Graze QLX Powercore, 2700 K, 60° x 30° Beam Angle, 610 mm (2 ft) |



Dimensional drawing

