

eW Graze QLX Powercore

eW Graze QLX Powercore, 4000 K, 60° x 30° Beam Angle, 610 mm (2 ft)

eW Graze QLX Powercore, 4000 K, 60° x 30° Beam Angle, 610 mm (2 ft)

eW Graze QLX Powercore is perfect for applications calling for a balance of cost and performance. Graze is a high-performance, exterior linear luminaire designed to highlight architectural features ranging from surface textures and molding details to archways and windows. Graze Essential White luminaries offer a single channel of white light. Available in 2700 K, 3000 K, 3500 K, 4000 K, and 5500 K. Multiple luminaire lengths, beam angles, output levels, and power consumption levels support a large range of façade or surface illumination applications. Low-profile housing, connectorized cabling, a universal power input range, and direct line voltage operation make Graze luminaires easy to install and operate.

Product data

General information	
Lamp family code	LED-HB [LED High Brightness]
Light source color	Neutral white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	Polycarbonate bowl/cover clear
Luminaire light beam spread	60° x 30°
Protection class IEC	Safety class I
CE mark	CE mark
UL mark	UL and cUL mark

Lifetime to 70% luminous flux	100000 h

Operating and electrical	
Input Voltage	100 to 277 V
Input Frequency	50 to 60 Hz

Controls and dimming	
Dimmable	Yes

eW Graze QLX Powercore

Mechanical and housing	
Housing Material	Aluminum extruded
Optical cover/lens material	Polycarbonate
Length	609 mm
Color	Aluminum

Approval and application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Vibration Standard	Complies with ANSI C136.31, 3G
Corrosion Resistance	Complies with ASTM B117 standard with special order. Please contact your Color Kinetics Lighting Sales rep for custom configurations.
FCC mark	FCC Class A
Vibration Rating	Complies with ANSI C136.31, 3G

Initial performance (IEC compliant)	
Init. Corr. Color Temperature	4000 K
Initial input power	28 W


Over time performance (IEC compliant)	
Lumen Maintenance 50% at 25°C Reported	60000
Lumen Maintenance 50% at 50°C Reported	60000
Lumen Maintenance 70% at 25°C Reported	60000
Lumen Maintenance 70% at 50°C Reported	60000

Application conditions	
Ambient temperature range	-40 to +50 °C

Product data	
Full product code	871829161131899
Order product name	BCS427 60x30/4000 L609
EAN/UPC - Product	8718291611318
Order code	523-000081-28
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	910503703775
Net Weight (Piece)	2.598 kg
Catalog Number	523-000081-28
Catalog Number Description	eW Graze QLX Powercore, 4000 K, 60° x 30° Beam Angle, 610 mm (2 ft)



Dimensional drawing



BCS427 60x30/4000 L609

eW Graze QLX Powercore

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.