

eW Graze EC Powercore

BCS428 4000 L609

eW Graze EC Powercore, 4000 K, 90° x 90° Beam Angle, 610 mm (2 ft)

Some exterior architectural details require a soft-edged volume fill of light. Graze EC Powercore combines this output with the proven, durable design of the Graze Powercore product family and low power consumption.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Light source colour	Neutral white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	PCF [Polycarbonate bowl/cover frosted]
Luminaire light beam spread	90° x 90°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL and cUL mark
Lifetime to 70% luminous flux	36000 h

Operating and Electrical	
Input Voltage	100 to 277 V
Input frequency	50 to 60 Hz

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Housing material	Aluminum extruded
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Length	609 mm
Colour	Aluminum

Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Vibration standard	Complies with ANSI C136.31, 3G
Vibration rating	Complies with ANSI C136.31, 3G

eW Graze EC Powercore

Initial Performance (IEC Compliant)	
Init. Corr. Colour Temperature	4000 K
Init. Colour rendering index	87
Initial input power	28 W

Over Time Performance (IEC Compliant)	
Lumen Maintenance 50% at 25 °C Reported	36000
Lumen Maintenance 50% at 50 °C Reported	36000
Lumen Maintenance 70% at 25 °C Reported	36000
Lumen Maintenance 70% at 50 °C Reported	36000


Application Conditions	
Ambient temperature range	-40 to +50 °C

Product Data	
Full product code	871829161197499

Order product name	BCS428 4000 L609
EAN/UPC – product	8718291611974
Order code	523-000082-04
SAP numerator – quantity per pack	1
Numerator – packs per outer box	4
SAP material	910503703811
SAP net weight (piece)	0.825 kg
Commercial Code	523-000082-04
Catalogue number description	eW Graze EC Powercore, 4000 K, 90° x 90° Beam Angle, 610 mm (2 ft)

IP66

Dimensional drawing



BCS428 4000 L609

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.