



Vaya Linear LP

BCP421 28x84 RGB L610 CE

Vaya Linear LP is a super slim outdoor linear luminaire for low-level grazing applications, with wide 120° beam or elliptical 28° x 84° optics. Its slim form factor is ideal for space-restricted applications with limited setback or allowable install height. The robust Vaya Linear LP offers a variety of color and white CCT options with either static on/off- or dynamic control options via standard DMX-512. The discreet design with integrated power supply and waterproof connectors makes wiring simple, fast and reliable.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Beam angle of light source	28 x 84 °
Light source color	Red, green and blue
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	Clear glass
Luminaire light beam spread	28°
CE mark	CE mark
UL mark	-
CQC mark	-
Lifetime to 70% luminous flux	50000 h
PSE mark	PSE mark
Operating and Electrical	
Input Voltage	100 to 240 V
Input Frequency	50 to 60 Hz

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Housing Material	Aluminum extruded
Optic material	Glass
Optical cover/lens material	Tempered glass
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Length	610 mm
Color	Dark gray
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK07 [2 J reinforced]
Vibration Standard	Complies with ANSI C136.31
Vibration Rating	Complies with ANSI C136.31

Datasheet, 2019, September 4 data subject to change


Vaya Linear LP

Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	288 lm
Initial input power	14 W
Over Time Performance (IEC Complian	nt)
Lumen Maintenance 50% at 25°C Calculated	100000
Lumen Maintenance 50% at 25°C Reported	60000
Lumen Maintenance 50% at 40°C Calculated	100000
Lumen Maintenance 50% at 40°C Reported	60000
Lumen Maintenance 70% at 25°C Calculated	100000
Lumen Maintenance 70% at 25°C Reported	60000
Lumen Maintenance 70% at 40°C Calculated	100000
Lumen Maintenance 70% at 40°C Reported	60000
Application Conditions	
Ambient temperature range	-40 to +40 °C

Product Data	
Full product code	871829162018199
Order product name	BCP421 28x84 RGB L610 CE
EAN/UPC - Product	8718291620181
Order code	910503704422
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	910503704422
Net Weight (Piece)	1.120 kg



Dimensional drawing



Vaya



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.