PHILIPS

Lighting



ColorGraze MX4 Powercore

BCS559 10x60 RGBW L609

RGBW - 10° x 60° - 610 mm

ColorGraze MX4 Powercore is a high-performance, exterior linear luminaire designed to highlight architectural features ranging from surface textures and moulding details to archways and windows. Graze RGBW luminaires add a separate white LED, creating better-quality whites compared to RGB. Graze RGBA luminaires add a separate amber LED which expands the available range of colours to include warmer tones such as rich gold, yellow and orange shades. Multiple fixture lengths and beam angles support a large range of façade or surface illumination applications. Low-profile housing, connectorised cabling, a universal power input range and direct line voltage operation make Graze luminaires easy to install and operate.

Product data

General Information	
Lamp family code	LED-HB [LED High Brightness]
Lamp colour code	RGBW
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	PC [Polycarbonate bowl/cover]
Luminaire light beam spread	10° x 60°
Protection class IEC	Safety class I (I)
CE mark	CE mark
UL mark	UL and cUL mark

Operating and Electrical	
Input voltage	100 to 277 V
Input frequency	50 to 60 Hz

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Housing material	Aluminum extruded
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate

ColorGraze MX4 Powercore

Length	610 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Vibration standard	Complies with ANSI C136.31, 3G
	Complies with ANSI C136.31, 3G

Initial Performance (IEC Compliant)

Initial luminous flux	1238 lm
Initial LED luminaire efficacy	34.9 lm/W
Initial input power	37 W

Over Time Performance (IEC Compliant)

Lumen Maintenance 50% at 25°C Reported	75000
Lumen Maintenance 50% at 50°C Reported	70000
Lumen Maintenance 70% at 25°C Calculated	100000
Lumen Maintenance 70% at 25°C Reported	70000
Lumen Maintenance 70% at 50°C Calculated	100000
Lumen Maintenance 70% at 50°C Reported	65000


Application Conditions

Ambient temperature range	-40 to +50 °C

Product Data

Full product code	871829161983399
Order product name	BCS559 10x60 RGBW L609
EAN/UPC – product	8718291619833
Order code	910503704687
Numerator – quantity per pack	1
Numerator – packs per outer box	4
Material no. (12NC)	910503704687
Net weight (piece)	2.700 kg

Dimensional drawing



Graze

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.