



CoreLine SlimDownlight

DN135B LED6S/840 PSR-E II WH

CoreLine SlimDownlight, 9 W, D68mm, 650 lm, 4000 K, Analog, Frosted, IP44

CoreLine slimdownlight delivers on the CoreLine promise of innovative, easy to use and high-quality indoor LED downlights. CoreLine slimdownlight is an innovative range of recessed and surface-mounted luminaires. It is designed to provide uniform lighting across multiple application areas. With instant energy savings and a longer lifetime, this is an environmentally friendly and cost saving solution. Its MultiColorTemp feature offers a choice of two color temperatures in a single luminaire. This makes it easy to select the right product, gives you the flexibility respond to customer preferences on site, and means fewer product codes on stock. Simple and easy installation means our slim downlight fits the same size cut-out, while the minimal built-in depth of 34mm makes this product an ideal space saving solution, especially for projects with limited fitting space. InterAct Ready option with integrated wireless communications in this family is available, to be used with InterAct gateways, sensors and software.

Product data

General Information		
Lamp family code	LED6S [LED Module, system flux 600 lm]	
Light source replaceable	No	
Number of gear units	1 unit	
Driver included	Yes	
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there	is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value.
Service tag	Yes	
Lighting Technology	LED	
Glow-wire test	Temperature 650 °C, duration 5 s	
Flammability mark	-	

CoreLine SlimDownlight

CE mark	Yes
ENEC mark	-
Warranty period	5 years
EU RoHS compliant	Yes
Value ladder	Performance

Light Technical

Luminous Flux	650 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	72 lm/W
Color rendering index (CRI)	>80
Number of light sources	1
Light source color	840 neutral white
Optic type	-
Optical cover type	Opal
Luminaire light beam spread	135°
Unified glare rating CEN	28

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	7 A
Inrush time	300 ms
Power Consumption	9 W
Power Factor (Fraction)	0.9
Connection	Push-in connector with 2 poles and pull relief
Cable	-
Number of products on MCB of 16 A type B	32

Temperature

Ambient temperature range	0 to +35 °C
---------------------------	-------------

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit regulating external
Control interface	Analog
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum
------------------	----------

Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	White
Optical cover finish	Frosted
Overall height	20 mm
Overall diameter	84 mm

Approval and Application

Ingress protection code	IP44 [Wire-protected, splash-proof]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38, 0.38) SDCM <5
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L70

Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	20% (depends on dimmer, ELV)
Suitable for random switching	Yes

Product Data

Order product name	DN135B LED6S/840 PSR-E II WH
Full product name	DN135B LED6S/840 PSR-E II WH
Full product code	871869938119699
Order code	910503910318
Material Nr. (12NC)	910503910318
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699381196
Numerator - Packs per outer box	24
EAN/UPC - Case	8718699381202

CoreLine SlimDownlight

Dimensional drawing

