



Ledinaire SlimDownlight

DN065B LED20S/830 PSU II WH

Ledinaire SlimDownlight, 23 W, 1850 lm, 3000 K, Frosted, IP20

The LEDINAIRE range contains a selection of popular off-the-shelf LED luminaires that come with the high Philips quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need

Product data

General Information		Connection	
Light source replaceable	No	Screw connector	
Lighting Technology	LED	Temperature	
Warranty period	3 years	Ambient temperature range	
Value ladder	Value	0 to +35 °C	
Light Technical		Controls and Dimming	
Luminous Flux	1,850 lm	Dimmable	
Correlated Color Temperature (Nom)	3000 K	No	
Luminous Efficacy (rated) (Nom)	80 lm/W	Driver/power unit/transformer	
Color rendering index (CRI)	>80	Power supply unit (On/Off)	
Light source color	830 warm white	Mechanical and Housing	
Luminaire light beam spread	90° x 90°	Housing Material	
Operating and Electrical		Plastic	
Line Frequency	50 or 60 Hz	Reflector material	
Input Frequency	50 or 60 Hz	Polycarbonate	
Power Consumption	23 W	Optic material	
Power Factor (Fraction)	0.8	Polycarbonate	
		Fixation material	
		Stainless steel	
		Housing Color	
		White	
		Optical cover finish	
		Frosted	
		Overall length	
		30 mm	
		Overall width	
		30 mm	
		Overall height	
		30 mm	

Ledinaire SlimDownlight

Overall diameter	225 mm
Dimensions (Height x Width x Depth)	30 x 30 x 30 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class II
Initial Performance (IEC Compliant)	
Initial chromaticity	(0.42, 0.40) SDCM <5
Power consumption tolerance	+/-10%

Product Data	
Order product name	DN065B LED20S/830 PSU II WH
Full product name	DN065B LED20S/830 PSU II WH
Full product code	871869938177699
Order code	910503910333
Material Nr. (12NC)	910503910333
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699381776
Numerator - Packs per outer box	12
EAN/UPC - Case	8718699381813

Dimensional drawing

