



Iridium LED Mini

BGS451 GRN20--2S/740 II WSO GR

Mini Iridium LED, LED GreenLine 2000 lm, 740 neutral white, Safety class II, Wide street optic, Grey

The second generation of compact Mini Iridium LED road-lighting luminaires offers a much wider scope of application thanks to a more powerful LED engine and brand new optics, which allow maximum energy savings in residential streets. Additional control devices can be fitted into the mast and communicate with the luminaire to further increase energy savings. This new generation of Mini Iridium LED also gives municipal authorities the freedom to change the atmosphere of the street thanks to the choice of different color temperatures (warm, neutral and cool white).

Product data

General Information			
Lamp family code	GRN20 [LED GreenLine 2000 lm]	Glow-wire test	Temperature 650 °C, duration 5 s
Light source replaceable	Yes	Flammability mark	-
Number of gear units	1 unit	CE mark	Yes
Driver included	Yes	ENEC mark	ENEC mark
Photocell	-	Warranty period	5 years
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value.	EU RoHS compliant	Yes
Light source engine type	LED	Light Technical	
Product family code	BGS451 [Mini Iridium LED]	Upward light output ratio	0.03
Lighting Technology	LED	Luminous Flux	2,004 lm
		Standard tilt angle posttop	10°
		Standard tilt angle side entry	0°
		Correlated Color Temperature (Nom)	4000 K
		Luminous Efficacy (rated) (Nom)	120 lm/W
		Color rendering index (CRI)	70
		Light source color	740 neutral white

Iridium LED Mini

Optical cover type	Polycarbonate bowl/cover
Luminaire light beam spread	180°
Optic type outdoor	Wide street optic

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	22 A
Inrush time	0.29 ms
Power Consumption	16.7 W
Power Factor (Fraction)	0.95
Connection	Internal connector
Cable	-
Number of products on MCB of 16 A type B	20

Temperature

Ambient temperature range	-20 to +35 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit regulating
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	Grey
Mounting device	Post-top for diameter 60 to 76 mm
Optical cover shape	Convex lens
Optical cover finish	Clear
Overall length	529 mm
Overall width	265 mm
Overall height	154.5 mm

Dimensional drawing

Effective projected area	0.032 m²
Dimensions (Height x Width x Depth)	155 x 265 x 529 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 8 kV common mode
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38,0.37) SDCM<5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 100000 h	L80

Application Conditions

Performance ambient temperature Tq	25 °C
------------------------------------	-------

Product Data

Order product name	BGS451 GRN20--2S/740 II WSO GR
Full product name	BGS451 GRN20--2S/740 II WSO GR
Full product code	871829134985300
Order code	910505002018
Material Nr. (12NC)	910505002018
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291349853
Numerator - Packs per outer box	1
EAN/UPC - Case	8718291349853

Iridium LED Mini

