PHILIPS

Lighting



SpeedStar

BGP323 GRN156--3S/740 I DM FG AL SI P3-7

SpeedStar Large, LED GreenLine 15600 lm, Distribution medium, Flat glass

Municipalities are under pressure to meet energy conservation goals by reducing their energy consumption and carbon footprint while complying with lighting norms and standards. Our SpeedStar LED luminaire addresses these fundamental issues and provides a solution to reduce the impact on our environment. SpeedStar is an energy-efficient luminaire requiring minimal maintenance and incorporating the easy-to-upgrade LEDGINE, which can be connected to lighting regulation systems for further energy savings. This carbon-neutral luminaire is the ideal solution for functional road and street lighting.

Product data

General Information	
Lamp family code	GRN156 [LED GreenLine 15600 lm]
Light source replaceable	Yes
Number of gear units	1 unit
Driver included	Yes
Photocell	Minicell (hole 20 mm) preset for 70 lx
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value.
Light source engine type	LED
Product family code	BGP323 [SpeedStar Large]
Lighting Technology	LED

Embedded control	-
CE mark	Yes
Warranty period	5 years
Flammability mark	-
ENEC mark	ENEC mark
Glow-wire test	Temperature 650 °C, duration 5 s
EU RoHS compliant	Yes

Light Technical	
Upward light output ratio	0.03
Luminous Flux	16,400 lm
Standard tilt angle posttop	5°
Standard tilt angle side entry	0°
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	137 lm/W

SpeedStar

Color rendering index (CRI)	70
Number of light sources	112
Light source color	740 neutral white
Optical cover type	Flat glass
Luminaire light beam spread	180°
Optic type outdoor	Distribution medium

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	53 A
Inrush time	0.3 ms
Power Consumption	120 W
Power Factor (Fraction)	0.8
Connection	-
Cable	-
Number of products on MCB of 16 A type B	3

Temperature

Ambient temperature range	-20 to +35 °C

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit regulating
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Glass
Fixation material	Aluminum
Housing Color	Silver
Mounting device	Universal for diameter 42 to 76 mm
Optical cover shape	Convex lens
Optical cover finish	Clear
Overall length	1,021 mm
Overall width	400 mm
Overall height	144 mm
Effective projected area	0.041 m²
Dimensions (Height x Width x Depth)	144 x 400 x 1021 mm
Parts color	All parts colored

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 6 kV common mode
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.380, 0.370) SDCM <3
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 100000 h	L80

Application Conditions


Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable

Product Data

Order product name	BGP323 GRN156--3S/740 I DM FG AL SI P3-7
Full product name	BGP323 GRN156--3S/740 I DM FG AL SI P3-7
Full product code	871829134492600
Order code	910505016358
Material Nr. (12NC)	910505016358
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291344926
Numerator - Packs per outer box	1
EAN/UPC - Case	8718291344926

SpeedStar

Dimensional drawing



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.