



CitySoul gen2 LED Large

BPP531 GRN185-/740 I DM FG CO GR D9 T35

CitySoul gen2 Large, LED GreenLine 18500 lm, Distribution medium, Flat glass

CitySoul gen2 LED is one of the most versatile and inspirational urban street lighting families designed by Philips to date. This highly efficient range delivers excellent lighting levels whilst also providing the right ambiance for all urban application areas, from the outskirts of the city right through to the city center. By evolving the modularity of the CitySoul family and adding new innovations like the Lyre and the Accent bracket, Philips has made this range the ideal toolbox for every urban context. The design is flatter, completely round, and the transitions with the spigot and bracket entirely flush, thereby giving your cityscape a coherent, elegant and discreet identity. Designed around its LED engine, CitySoul gen2 LED is highly efficient and easy to maintain. It comes in two sizes and is suitable for side-entry, post-top, catenary and suspended mounting.

Product data

General Information	
Lamp family code	GRN185 [LED GreenLine 18500 lm]
Light source replaceable	Yes
Number of gear units	Unit
Driver included	Yes
Remarks	* At extreme ambient temperatures the
	luminaire might automatically dim down to
	protect components
Light source engine type	LED
Product family code	BPP531 [CitySoul gen2 Large]

Lighting Technology	LED
Value ladder	Performance
Embedded control	-
CE mark	Yes
Warranty period	5 years
Flammability mark	-
ENEC mark	ENEC mark
Glow-wire test	Temperature 650 °C, duration 30 s
EU RoHS compliant	Yes

Datasheet, 2023, December 5 data subject to change

CitySoul gen2 LED Large

Light Technical	
Upwards light output ratio	0.03
Luminous Flux	14,995 lm
Standard tilt angle post-top	0°
Standard tilt angle side entry	0°
Correlated Colour Temperature	4000 K
Luminous efficacy (rated) (nom.)	115 lm/W
Colour rendering index (CRI)	>70
Light source colour	740 neutral white
Optical cover type	Flat glass
Luminaire light beam spread	180°
Optic type outdoor	Distribution medium
opin type sutuso.	Distribution median.
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	53 A
Inrush time	0.3 ms
Power Consumption	130 W
Power Factor (Fraction)	0.8
Connection	-
Cable	-
Number of products on MCB of 16 A ty	pe B 11
Temperature	
-	-40 to +50 °C
Ambient temperature range	-40 to +50 °C
-	-40 to +50 °C
Ambient temperature range	-40 to +50 °C Yes
Ambient temperature range Controls and Dimming	Yes
Ambient temperature range Controls and Dimming Dimmable	Yes
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer	Yes Power supply unit with DALI interface
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface	Yes Power supply unit with DALI interface DALI
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface	Yes Power supply unit with DALI interface DALI
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output	Yes Power supply unit with DALI interface DALI
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing	Yes Power supply unit with DALI interface DALI No
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing Housing material	Yes Power supply unit with DALI interface DALI No
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing Housing material Reflector material	Yes Power supply unit with DALI interface DALI No Aluminium -
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing Housing material Reflector material Optic material	Yes Power supply unit with DALI interface DALI No Aluminium - Polymethyl methacrylate
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing Housing material Reflector material Optic material Optical cover/lens material	Yes Power supply unit with DALI interface DALI No Aluminium - Polymethyl methacrylate Polymethyl methacrylate
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing Housing material Reflector material Optic material Optical cover/lens material Fixation material	Yes Power supply unit with DALI interface DALI No Aluminium - Polymethyl methacrylate Polymethyl methacrylate Aluminium
Ambient temperature range Controls and Dimming Dimmable Driver/power unit/transformer Control interface Constant light output Mechanical and Housing Housing material Reflector material Optic material Optical cover/lens material Fixation material Housing Colour	Yes Power supply unit with DALI interface DALI No Aluminium - Polymethyl methacrylate Polymethyl methacrylate Aluminium Grey

Overall length	720 mm	
Overall width	628 mm	
Overall height	99 mm	
Effective projected area	0.028 m²	
Dimensions (height x width x depth)	99 x 628 x 720 mm	
Parts colour	Cover painted	
Approval and Application		
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK08 [5 J vandal-protected]	
Surge Protection (Common/Differential)	Luminaire surge protection level up to 6 kV	
	differential mode and 8 kV common mode	
Protection class IEC	Safety class I	
Photobiological risk	Photobiological risk group 1 @200mm to	
	EN62778	
Initial Performance (IEC Compliant)		
Luminous flux tolerance	+/-10%	
Initial chromaticity	(0.38,0.37) SDCM<5	
Power consumption tolerance	+/-10%	
Init. Color Rendering Index Tolerance	+/-2	
Over Time Performance (IEC Compliant)		
Driver failure rate at 5,000 hours	0.15 %	
Application Conditions		
Maximum dim level	10%	
Product Data		
Order product name	BPP531 GRN185-/740 I DM FG CO GR D9	
•	, T35	
Full product name	BPP531 GRN185-/740 I DM FG CO GR D9	
	T35	
Full EOC	871869661349800	
Order code	61349800	
Material no. (12 NC)	910505016889	
SAP numerator – quantity per pack	1	
EAN/UPC — Product/Case	8718696613498	
Numerator – packs per outer box	1	
EAN/UPC - Case	8718696613498	
LAN, OF C - Case		

CitySoul gen2 LED Large

Dimensional drawing



