



Maxos accessories

9MX056 EC7 (10PCS)

ACC MAXOS

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Product data

| General Information | |
|--------------------------|--------------------|
| Accessory color | - |
| Product family code | 9MX056 [ACC MAXOS] |
| | |
| Operating and Electrical | |
| Input Voltage | 220 to 240 V |
| Line Frequency | 50 to 60 Hz |
| | |
| Approval and Application | |
| Ingress protection code | - |
| Protection class IEC | Safety class I |

| Product Data | |
|---------------------------------|--------------------|
| Order product name | 9MX056 EC7 (10PCS) |
| Full product name | 9MX056 EC7 (10PCS) |
| Full product code | 403073203217400 |
| Order code | 910606293921 |
| Material Nr. (12NC) | 910606293921 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 4030732032174 |
| Numerator - Packs per outer box | 1 |
| EAN/UPC - Case | 4030732032174 |
| | |

Datasheet, 2024, January 22 data subject to change