



Maxos, TL5 electrical units

4MX691 1xTL5-28W HFP WH

MAXOS LTT5, 1, TL5, 28 W, HF Performer

The electrical units for MAXOS TL5 are designed for quick and reliable click-on mounting. They are made of steel, with a white or silver coating. For electrical connection to the trunking a connector block is mounted. The electrical units are equipped with HF-P electronic ballasts or HF-R dimming ballasts, allowing the light output of the lamps to be regulated from 3% to 100%. HF-R units must be mounted to 7-wire trunking sections. The electrical units can hold 1 or 2 TL5 lamps. Emergency lighting: Special electrical units equipped with an emergency battery pack for 1 or 3 hours (EL1/EL3) are available. These units must be used with 7-wire trunking sections. If trunkings with double wiring are used one flat ribbon cable can be connected to the central battery. This provides a completely separate emergency lighting circuit. Only than standard electrical units equipped with electronic ballasts can be used for emergency lighting. The electrical units can be combined with a complete range of reflectors. Moreover, TL5 offers significant efficiency gains compared to TL-D, and these gains increase when the ambient temperature is high.

Product data

General Information	
Lamp family code	TL5 [TL5]
Gear	HFP [HF Performer]
Product family code	4MX691 [MAXOS LTT5]
CE mark	Yes
Flammability mark	For mounting on normally flammable surfaces
ENEC mark	ENEC mark

Light Technical	
Number of light sources	1
Light source color	-
Optic type	-
Optical cover type	-
Operating and Electrical	
Power Consumption	28 W

Maxos, TL5 electrical units

Connection	-
Mechanical and Housing	
Housing Color	White
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Protection class IEC	Safety class I
Application Conditions	
Suitable for random switching	Not applicable

Product Data	
Order product name	4MX691 1xTL5-28W HFP WH
Full product name	4MX691 1xTL5-28W HFP WH
Full product code	403073258273099
Order code	58273099
Material Nr. (12NC)	910621103026
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	4030732582730
Numerator - Packs per outer box	6
EAN/UPC - Case	4030732197859

Dimensional drawing

