



Maxos, TL5 electrical units

4MX6911xTL5-35W HFP WH

MAXOS LTT5, 1, TL5, 35 W, HF Performer, White

The electrical units for Maxos TL5 are designed for quick and reliable click-on mounting. They are made of steel with a white or silver finish. A connector block is mounted for electrical connection to the trunking. The electrical units are equipped with HFP electronic ballasts, HFR dimming ballasts or HF-DALI ballasts. HFR and HF-DALI units must be mounted to 7-wire trunking sections. The electrical units can hold 1 or 2 TL5 lamps. Emergency lighting – Special electrical units equipped with an emergency battery pack for 1 or 3 hours (EL1/EL3) are available. These units must be used with 7-wire light-line sections. If light lines with double wiring are used, one flat ribbon cable can be connected to the central battery. This provides a completely separate emergency lighting circuit. The trunking is available with a complete range of interchangeable components that optimize flexibility. Moreover, TL5 offers significant efficiency gains compared to TL-D and these gains increase when the ambient temperature is high.

Product data

General Information	
Lamp family code	TL5 [TL5]
Gear	HFP [HF Performer]
Product family code	4MX691 [MAXOS LTT5]
CE mark	Yes
Flammability mark	For mounting on normally flammable surfaces
ENEC mark	ENEC mark

Light Technical	
Number of light sources	1
Light source color	-
Optic type	-
Optical cover type	-
Operating and Electrical	
Power Consumption	35 W

Datasheet, 2023, September 4 data subject to change

Maxos, TL5 electrical units

Connection	=
Mechanical and Housing	
Housing Color	White
Overall length	1,479 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Protection class IEC	Safety class I
Application Conditions	
Suitable for random switching	Not applicable

Product Data	
Order product name	4MX691 1xTL5-35W HFP WH
Full product name	4MX691 1xTL5-35W HFP WH
Full product code	403073258286099
Order code	910621106026
Material Nr. (12NC)	910621106026
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	4030732582860
Numerator - Packs per outer box	6
EAN/UPC - Case	4030732197873

Dimensional drawing



