



Maxos LED Performer

4MX900 491 LED40S/830 PSU WB SI

Maxos LED Performer, LED module, system flux 4000 lm, 830 warm white, Power supply unit (On/Off), Wide beam, Silver

Customers want to save energy and reduce cost compared to what they are used to with conventional lighting. At the same time, excellent lighting conditions are needed: in industrial environments, to guarantee safety and productivity; and in retail environments, to make the merchandise stand out and attract shoppers. Maxos LED Performer is an extremely flexible solution that delivers low energy consumption and excellent beam shaping at an attractive investment level.

Product data


| General Information | | Warranty period | |
|--------------------------|---|----------------------------------|-----------------------------------|
| Lamp family code | LED40S [LED module, system flux 4000 lm] | Flammability mark | - |
| Light source replaceable | No | ENEC mark | ENEC mark |
| Number of gear units | Unit | Glow-wire test | Temperature 650 °C, duration 30 s |
| Driver included | Yes | EU RoHS compliant | Yes |
| Remarks | * - According to the Lighting Europe guidance paper 'Evaluating performance of LED based luminaires – January 2018': statistically there is no relevant difference in lumen maintenance between the B50 and, for example, the B10. Therefore, the median useful life (B50) value also represents the B10 value. | Light Technical | |
| Product family code | 4MX900 [Maxos LED Performer] | Luminous Flux | 4,000 lm |
| Lighting Technology | LED | Saturated Red (R9) | <50 |
| Value ladder | Performance | Correlated Colour Temperature | 3000 K |
| CE mark | Yes | Luminous efficacy (rated) (nom.) | 151 lm/W |
| | | Colour rendering index (CRI) | ≥80 |
| | | Beam angle of light source | 120 degree(s) |
| | | Light source colour | 830 warm white |
| | | Optic type | Wide beam |
| | | Luminaire light beam spread | 90° |

Maxos LED Performer

| | |
|--|----------------------------|
| Unified Glare Rating (CEN) | Not applicable |
| Operating and Electrical | |
| Input Voltage | 220 to 240 V |
| Line Frequency | 50 to 60 Hz |
| Inrush current | 17.8 A |
| Inrush time | 0.282 ms |
| Power Consumption | 25.2 W |
| Power Factor (Fraction) | 0.9 |
| Connection | Connection unit 3-pole |
| Cable | - |
| Number of products on MCB of 16 A type B | 24 |
| Temperature | |
| Ambient temperature range | -20 to +40 °C |
| Controls and Dimming | |
| Dimmable | No |
| Driver/power unit/transformer | Power supply unit (On/Off) |
| Control interface | - |
| Constant light output | No |
| Mechanical and Housing | |
| Housing material | Aluminium |
| Reflector material | - |
| Optic material | Polymethyl methacrylate |
| Optical cover/lens material | Polymethyl methacrylate |
| Fixation material | Steel |
| Housing Colour | Silver |
| Optical cover/lens finish | Clear |
| Overall length | 1,479 mm |
| Overall width | 87 mm |
| Overall height | 82 mm |
| Dimensions (height x width x depth) | 82 x 87 x 1479 mm |
| Approval and Application | |
| Ingress protection code | IP40 [Wire-protected] |
| Mech. impact protection code | IK02 [0.2 J standard] |

| | |
|---|--|
| Sustainability rating | - |
| Protection class IEC | Safety class I |
| Photobiological risk | Photobiological risk group 0 @200mm to EN62778 |
| Initial Performance (IEC Compliant) | |
| Luminous flux tolerance | +/-10% |
| Initial chromaticity | (0.43, 0.40) SDCM <3.5 |
| Power consumption tolerance | +/-10% |
| Over Time Performance (IEC Compliant) | |
| Control gear failure rate at median useful life 50,000 h | 5 % |
| Control gear failure rate at median useful life 100,000 h | 10 % |
| Lumen maintenance at median useful life* 50,000 h | L80 |
| Lumen maintenance at median useful life* 100,000 h | L80 |
| Application Conditions | |
| Performance ambient temperature Tq | 25 °C |
| Maximum dim level | Not applicable |
| Suitable for random switching | Not applicable |
| Product Data | |
| Order product name | 4MX900 491 LED40S/830 PSU WB SI |
| Full product name | 4MX900 491 LED40S/830 PSU WB SI |
| Full EOC | 403073266488799 |
| Order code | 66488799 |
| Material no. (12 NC) | 910629141626 |
| SAP numerator – quantity per pack | 1 |
| EAN/UPC – Product/Case | 4030732664887 |
| Numerator – packs per outer box | 2 |
| EAN/UPC - Case | 4030732262700 |

Dimensional drawing



Maxos LED Performer

