



# Maxos LED

## 4MX866 581 LED66S/840 PSD WB WH C-2R

MAXOS LED EM 1H6S, Generation 4, LED module, system flux 6600 lm, 840 neutral white, Power supply unit with DALI interface, Wide beam, White, Connector with 2 additional wires for light regulation

Customers in the industrial and retail sectors are looking for general lighting solutions with a justifiable payback, while meeting all relevant norms for supermarkets and industry applications. For a limited investment, Maxos LED Industry offers best-in-class energy savings while delivering high lux levels at the required color temperatures and glare factors. The minimalistic Maxos LED Industry system comprises exchangeable mid-power LED boards mounted on a standard Maxos trunking rail. A choice of wide and medium-beam lenses means flexibility in light distribution. Compared with a conventional fluorescent installation, this highly efficient LED solution offers full payback in less than three years. And the benefits keep coming: the use of our upgradable LED engine platform makes Maxos LED Industry a truly future-proof solution.

### Product data

| General Information      |   |   |
|--------------------------|---|---|
| Lamp family code         | LED66S [LED module, system flux 6600 lm]  |   |
| Cap-Base                 | - [-]   |   |
| Light source replaceable | No  |   |
| Number of gear units     | 1 unit  |   |
| Gear                     | -   |   |
| Driver included          | Yes   |   |
| Remarks                  | *-Per Lighting Europe guidance paper<br>"Evaluating performance of LED based<br>luminaires - January 2018": statistically there | is no relevant difference in lumen<br>maintenance between B50 and for example<br>B10. Therefore, the median useful life (B50)<br>value also represents the B10 value. |
| Service tag              |   | Yes   |
| Product family code      |   | 4MX866 [MAXOS LED EM 1H6S]  |
| Lighting Technology      |   | LED   |
| Value ladder             |   | Performance   |
| CE mark                  |   | Yes   |
| Warranty period          |   | 5 years   |

# Maxos LED

|                   |                                   |
|-------------------|-----------------------------------|
| Flammability mark | -                                 |
| ENEC mark         | ENEC mark                         |
| Glow-wire test    | Temperature 650 °C, duration 30 s |
| EU RoHS compliant | Yes                               |

## Light Technical

|                                    |                                    |
|------------------------------------|------------------------------------|
| Luminous Flux                      | 6,600 lm                           |
| Correlated Color Temperature (Nom) | 4000 K                             |
| Luminous Efficacy (rated) (Nom)    | 147 lm/W                           |
| Color rendering index (CRI)        | ≥80                                |
| Number of light sources            | 1                                  |
| Beam angle of light source         | 120 degree(s)                      |
| Light source color                 | 840 neutral white                  |
| Optic type                         | Wide beam                          |
| Optical cover type                 | Polymethyl methacrylate bowl/cover |
| Luminaire light beam spread        | 90°                                |
| Unified glare rating CEN           | Not applicable                     |

## Operating and Electrical

|  |  |
|--|--|
| Input Voltage                            | 220-240 V  |
| Line Frequency                           | 50 to 60 Hz  |
| Inrush current                           | 21 A   |
| Inrush time                              | 0.280 ms   |
| Power Consumption                        | 45 W   |
| Power Factor (Fraction)                  | 0.9  |
| Connection                               | Connector with 2 additional wires for light regulation |
| Cable                                    | -  |
| Number of products on MCB of 16 A type B | 24   |

## Temperature

|                           |               |
|---------------------------|---------------|
| Ambient temperature range | -20 to +35 °C |
|---------------------------|---------------|

## Controls and Dimming

|                               |                                       |
|-------------------------------|---------------------------------------|
| Dimmable                      | Yes                                   |
| Driver/power unit/transformer | Power supply unit with DALI interface |
| Control interface             | DALI                                  |
| Constant light output         | No                                    |

## Mechanical and Housing

|                    |       |
|--------------------|-------|
| Housing Material   | Steel |
| Reflector material | -     |

|                                     |                         |
|-------------------------------------|-------------------------|
| Optic material                      | Polymethyl methacrylate |
| Optical cover material              | Polymethyl methacrylate |
| Fixation material                   | Steel                   |
| Housing Color                       | White                   |
| Optical cover finish                | Clear                   |
| Overall length                      | 1,528 mm                |
| Overall width                       | 63 mm                   |
| Overall height                      | 50 mm                   |
| Dimensions (Height x Width x Depth) | 50 x 63 x 1528 mm       |

## Approval and Application

|                              |                         |
|------------------------------|-------------------------|
| Ingress protection code      | IP20 [Finger-protected] |
| Mech. impact protection code | IK02 [0.2 J standard]   |
| Protection class IEC         | Safety class I          |

## Initial Performance (IEC Compliant)

|                             |                        |
|-----------------------------|------------------------|
| Luminous flux tolerance     | +/-10%                 |
| Initial chromaticity        | (0.38, 0.38) SDCM <3.5 |
| Power consumption tolerance | +/-10%                 |

## Over Time Performance (IEC Compliant)

|   |     |
|---|-----|
| Control gear failure rate at median useful life 50000 h | 5 % |
| Lumen maintenance at median useful life* 50000 h        | L80 |

## Application Conditions

|                                    |                |
|------------------------------------|----------------|
| Performance ambient temperature Tq | 25 °C          |
| Maximum dim level                  | 1%             |
| Suitable for random switching      | Not applicable |

## Product Data

|                                 |                                      |
|---------------------------------|--------------------------------------|
| Order product name              | 4MX866 581 LED66S/840 PSD WB WH C-2R |
| Full product name               | 4MX866 581 LED66S/840 PSD WB WH C-2R |
| Full product code               | 403073267385899                      |
| Order code                      | 910629165326                         |
| Material Nr. (12NC)             | 910629165326                         |
| Numerator - Quantity Per Pack   | 1                                    |
| EAN/UPC - Product/Case          | 4030732673858                        |
| Numerator - Packs per outer box | 3                                    |
| EAN/UPC - Case                  | 4030732275052                        |

## Maxos LED

### Dimensional drawing

