



## **Maxos accessories**

## 9MX056 EP SI SET

## ACC MAXOS, Silver

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

## **Product data**

General Information	
Accessory color	Silver
Product family code	9MX056 [ACC MAXOS]
Approval and Application	
Ingress protection code	-
Protection class IEC	-
Product Data	
Order product name	9MX056 EP SI SET
-	

Full product name	9MX056 EP SI SET
Full product code	403073210825100
Order code	10825100
Material Nr. (12NC)	910683002126
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	4030732108251
Numerator - Packs per outer box	1
EAN/UPC - Case	4030732108251

Datasheet, 2023, April 16 data subject to change