



Koffer² LED Mini

BGP060 GRN29--3S/740 II WSO FM GR CLO

Mini Koffer2 LED, LED GreenLine 2900 lm, 740 neutral white, Safety class II, Wide street optic, Grey, Constant light output

Koffer² is an archetypal modern road lighting luminaire which meets the needs of today's road users and operators. Total cost over lifetime was a key consideration in the development of Koffer². The future-proof luminaire delivers outstanding optical performance, enabling optimum spacing and energy efficiency, and is easy to install and maintain. With its rectangular shape, Koffer² offers an alternative to rounded luminaires. It is available in three sizes – for mounting heights from 3.5 to 12 meters – and with dedicated masts and brackets, making it equally suitable for integration into modern urban environments or more traditional lighting designs. The Koffer² family accommodates CosmoPolis white-light technology and LED-enabled versions. Each Koffer² luminaire is fully recyclable; only the light source and driver have to be recycled separately.

Product data

General Information			
Lamp family code	GRN29 [LED GreenLine 2900 lm]	Light source engine type	LED
Light source replaceable	Yes	Product family code	BGP060 [Mini Koffer2 LED]
Number of gear units	1 unit	Lighting Technology	LED
Driver included	Yes	Embedded control	Constant light output
Photocell	-	CE mark	Yes
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value.	Warranty period	5 years
		Flammability mark	-
		ENEC mark	ENEC mark
		EU RoHS compliant	Yes
Light Technical			
		Upward light output ratio	0.03

Koffer² LED Mini

Luminous Flux	2.905 lm
Standard tilt angle posttop	10°
Standard tilt angle side entry	0°
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	126 lm/W
Color rendering index (CRI)	70
Light source color	740 neutral white
Optical cover type	Polycarbonate bowl/cover
Luminaire light beam spread	180°
Optic type outdoor	Wide street optic

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Initial CLO power consumption	18.4 W
Average CLO power consumption	20.7 W
End CLO power consumption	23 W
Inrush current	22 A
Inrush time	0.29 ms
Power Consumption	23 W
Power Factor (Fraction)	0.95
Connection	Internal connector
Cable	-
Number of products on MCB of 16 A type B	20

Temperature

Ambient temperature range	-20 to +35 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit regulating with constant light output
Constant light output	Yes

Mechanical and Housing

Housing Material	Aluminum
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Aluminum
Housing Color	Grey
Mounting device	Post-top for diameter 60 to 76 mm
Optical cover shape	Convex lens

Optical cover finish	Clear
Overall length	511 mm
Overall width	264 mm
Overall height	111 mm
Effective projected area	0.032 m²
Dimensions (Height x Width x Depth)	111 x 264 x 511 mm
Parts color	-

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 8 kV common mode
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38,0.37) SDCM<5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 100000 h	L80

Application Conditions

Performance ambient temperature Tq	25 °C
------------------------------------	-------

Product Data

Order product name	BGP060 GRN29--3S/740 II WSO FM GR CLO
Full product name	BGP060 GRN29--3S/740 II WSO FM GR CLO
Full product code	871829197953100
Order code	910770100572
Material Nr. (12NC)	910770100572
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291979531
Numerator - Packs per outer box	1
EAN/UPC - Case	8718291979531

Koffer² LED Mini

Dimensional drawing

