



# ClearWay

## BGP303 LED35-3S/740 PSR II STD 42/60

ClearWay, LED module 3500 lm, 740 neutral white, Power supply unit regulating, Safety class II, Philips standard surge protection level, Universal for diameter 42 to 60 mm

LED technology represents a breakthrough in lighting in many different respects. The light quality provided by LEDs, for example, has made our roads safer, while the tremendous efficacy of LEDs is helping cities reduce their energy bills. At Philips, we believe we can make even more roads safer, and help more municipalities achieve their goal of reducing energy consumption. That's why we have developed ClearWay – a LED road luminaire that is affordable yet does not compromise on light quality and energy efficiency.

### Product data

General Information		Warranty period	
Lamp family code	LED35 [LED module 3500 lm]	Warranty period	3 years
Light source replaceable	No	EU RoHS compliant	No
Number of gear units	1 unit	Embedded control	-
Gear	EBP [Electronic Primalume]	Light Technical	
Driver included	Yes	Upward light output ratio	0
Photocell	-	Luminous Flux	3,074 lm
Light source engine type	LED	Standard tilt angle posttop	0°
Product family code	BGP303 [ClearWay]	Standard tilt angle side entry	0°
Lighting Technology	LED	Correlated Color Temperature (Nom)	4000 K
Glow-wire test	Temperature 960 °C, duration 5 s	Luminous Efficacy (rated) (Nom)	106 lm/W
Flammability mark	For mounting on normally flammable surfaces	Color rendering index (CRI)	>70
CE mark	Yes	Number of light sources	1
ENEC mark	ENEC mark	Light source color	740 neutral white
		Optical cover type	Flat glass

Luminaire light beam spread	-
Optic type outdoor	Distribution medium

## Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Inrush current	22 A
Inrush time	0.29 ms
Power Consumption	29 W
Power Factor (Fraction)	0.98
Connection	Screw connection block 5-pole
Cable	-

Number of products on MCB of 16 A type B 20

## Temperature

Ambient temperature range	-30 to +35 °C
---------------------------	---------------

## Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit regulating
Constant light output	No

## Mechanical and Housing

Housing Material	Aluminum
Reflector material	Polycarbonate
Optic material	Acrylate
Optical cover material	Tempered glass
Fixation material	Steel
Housing Color	Gray
Mounting device	Universal for diameter 42 to 60 mm
Optical cover shape	Flat
Optical cover finish	Clear
Overall length	481 mm

Overall width	330 mm
Overall height	97 mm
Effective projected area	0.029 m <sup>2</sup>
Dimensions (Height x Width x Depth)	97 x 330 x 481 mm

## Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Philips standard surge protection level
Protection class IEC	Safety class II

## Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.380, 0.380) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

## Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	0.5 %
-------------------------------	-------

## Product Data

Order product name	BGP303 LED35-3S/740 PSR II STD 42/60
Full product name	BGP303 LED35-3S/740 PSR II STD 42/60
Full product code	871829188451400
Order code	910925438763
Material Nr. (12NC)	910925438763
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291884514
Numerator - Packs per outer box	1
EAN/UPC - Case	8718291884514

