



Iridium² LED Medium

BGP352 ECO99-3S/740 II DM AL GR LS-8 50%

Iridium² LED Medium, LED EconomyLine 9900 lm, 740 neutral white, Safety class II, Distribution medium, Grey, LumiStep dimming 8 hours

Iridium² is a family of road-lighting luminaires designed for performance and sustainability. Depending on the application and budget, customers can start with LED, electronic HID or a mix of both technologies with the same luminaire. Whatever the initial choice, Iridium²'s modularity allows customers to upgrade their installations (LED to LED or e-HID to LED) whenever they want, simply by changing the light engine. The integration of LEDGINE, brand new HID optics, electronic gear and controls is a response to the growing demand for energy savings. The new Iridium² HID optics are designed to deliver best-in-class lighting performance while offering tremendous flexibility in application. All these features, combined with Iridium²'s ease of installation and maintenance, ensure that customers enjoy low cost of ownership.

Product data

General Information			
Lamp family code	ECO99 [LED EconomyLine 9900 lm]	B10. Therefore, the median useful life (B50) value also represents the B10 value.	
Light source replaceable	Yes	Light source engine type	LED
Number of gear units	1 unit	Product family code	BGP352 [Iridium² LED Medium]
Driver included	Yes	Lighting Technology	LED
Photocell	-	Embedded control	LumiStep dimming 8 hours
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example		
		CE mark	Yes
		Warranty period	5 years
		Flammability mark	-
		ENEC mark	-

Iridium² LED Medium

EU RoHS compliant	No
Light Technical	
Upward light output ratio	0
Luminous Flux	8,559 lm
Standard tilt angle posttop	0°
Standard tilt angle side entry	0°
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	101 lm/W
Color rendering index (CRI)	70
Number of light sources	40
Light source color	740 neutral white
Optical cover type	Flat glass
Luminaire light beam spread	150° x 62°
Optic type outdoor	Distribution medium
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	53 A
Inrush time	0.3 ms
Power Consumption	85 W
Power Factor (Fraction)	0.9
Connection	Plug-in connector 3-pole Wieland/Adels compatible
Cable	-
Number of products on MCB of 16 A type B	8
Temperature	
Ambient temperature range	-25 to +25 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit with DynaDimmer
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum die cast
Reflector material	Acrylate
Optic material	Polycarbonate
Optical cover material	Tempered glass
Fixation material	Stainless steel
Housing Color	Grey
Mounting device	Universal for diameter 48 to 76 mm

Optical cover shape	Flat
Optical cover finish	Clear
Overall length	751 mm
Overall width	358 mm
Overall height	183 mm
Effective projected area	0.08 m²
Dimensions (Height x Width x Depth)	183 x 358 x 751 mm
Parts color	All parts colored
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Surge Protection (Common/Differential)	Philips standard surge protection level
Protection class IEC	Safety class II
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-7%
Initial chromaticity	(0.380, 0.380) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 75000 h	7.5 %
Lumen maintenance at median useful life* 75000 h	L80
Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	50%
Product Data	
Order product name	BGP352 ECO99-3S/740 II DM AL GR LS-8 50%
Full product name	BGP352 ECO99-3S/740 II DM AL GR LS-8 50%
Full product code	871829197667700
Order code	910925439603
Material Nr. (12NC)	910925439603
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291976677
Numerator - Packs per outer box	1
EAN/UPC - Case	8718291976677

Iridium² LED Medium

Dimensional drawing

