

# Iridium gen3 LED Large

## BGP383 LW10 GRN145/740 II DM AL 7035 SP

Iridium gen3 Large, CityTouch with 10 years service contract, LED GreenLine 14500 lm, 740 neutral white, Safety class II, Distribution medium, Spigot

Iridium gen3 is the first truly intelligent luminaire designed for seamless connectivity. No hassle in commissioning – just install the luminaire and control it from a distance through CityTouch management software. Remote light management made easy! The new 'plug & play' concept has been designed to ensure safe and easy installation in just three steps: 1. Install the spigot, 2. Plug in the mains, 3. Tilt and close the luminaire. The luminaire's high efficiency at system level ensures significant energy savings compared to existing conventional installations, offering a fast payback. Thanks to its wide choice of lumen packages, optics and color temperatures, Iridium gen3 fits most applications in residential areas. The luminaire's neo-classical design guarantees a consistent look and feel for your surroundings.

### Product data

| General Information | |
|---|---|
| **Lamp family code** | GRN145 [LED GreenLine 14500 lm] |
| **Light source replaceable** | Yes |
| **Number of gear units** | 1 unit |
| **Gear** | EB [Electronic] |
| **Driver included** | Yes |
| **Photocell** | - |
| **Remarks** | *-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value. |
| **Light source engine type** | LED |
| **Product family code** | BGP383 [Iridium gen3 Large] |
| **Lighting Technology** | LED |
| **Embedded control** | - |
| **CE mark** | Yes |
| **Warranty period** | 5 years |

# Iridium gen3 LED Large

| | |
|---|---|
| **Flammability mark** | - |
| **ENEC mark** | ENEC mark |
| **Glow-wire test** | Temperature 650 °C, duration 5 s |
| **EU RoHS compliant** | No |

## Light Technical

| | |
|---|---|
| **Upward light output ratio** | 0 |
| **Luminous Flux** | 13,340 lm |
| **Standard tilt angle posttop** | 0° |
| **Standard tilt angle side entry** | 0° |
| **Correlated Color Temperature (Nom)** | 4000 K |
| **Luminous Efficacy (rated) (Nom)** | 155 lm/W |
| **Color rendering index (CRI)** | 70 |
| **Light source color** | 740 neutral white |
| **Optical cover type** | Polycarbonate bowl/cover |
| **Luminaire light beam spread** | 152° |
| **Optic type outdoor** | Distribution medium |

## Operating and Electrical

| | |
|---|---|
| **Input Voltage** | 220 to 240 V |
| **Line Frequency** | 50 to 60 Hz |
| **Inrush current** | 53 A |
| **Inrush time** | 0.3 ms |
| **Power Consumption** | 86 W |
| **Power Factor (Fraction)** | 0.97 |
| **Connection** | Screw connection block 3-pole |
| **Cable** | - |
| **Number of products on MCB of 16 A type B** | 8 |

## Temperature

| | |
|---|---|
| **Ambient temperature range** | -40 to +50 °C |

## Controls and Dimming

| | |
|---|---|
| **Dimmable** | Yes |
| **Driver/power unit/transformer** | Power supply unit regulating external |
| **Control interface** | GPRS network |
| **Constant light output** | No |

## Mechanical and Housing

| | |
|---|---|
| **Housing Material** | Aluminum |
| **Reflector material** | - |
| **Optic material** | Polycarbonate |
| **Optical cover material** | Polycarbonate |
| **Fixation material** | Aluminum |
| **Housing Color** | RAL (to be defined) |
| **Mounting device** | Spigot |
| **Optical cover shape** | Flat |
| **Optical cover finish** | Textured |
| **Overall length** | 750 mm |
| **Overall width** | 355 mm |
| **Overall height** | 157 mm |
| **Effective projected area** | 0.039 m² |
| **Dimensions (Height x Width x Depth)** | 157 x 355 x 750 mm |
| **Parts color** | All parts colored |

## Approval and Application

| | |
|---|---|
| **Ingress protection code** | IP66 [Dust penetration-protected, jet-proof] |
| **Mech. impact protection code** | IK09 [10 J] |
| **Surge Protection (Common/Differential)** | 4/4 kV |
| **Protection class IEC** | Safety class II |

## Initial Performance (IEC Compliant)

| | |
|---|---|
| **Luminous flux tolerance** | +/-7% |
| **Initial chromaticity** | (0.38, 0.38) SDCM <5 |
| **Power consumption tolerance** | +/-10% |
| **Init. Color Rendering Index Tolerance** | +/-2 |

## Over Time Performance (IEC Compliant)

| | |
|---|---|
| **Control gear failure rate at median useful life 100000 h** | 10 % |
| **Lumen maintenance at median useful life* 100000 h** | L80 |

## Application Conditions


| | |
|---|---|
| **Performance ambient temperature Tq** | 25 °C |
| **Maximum dim level** | 0% (digital) |

## Product Data

| | |
|---|---|
| **Order product name** | BGP383 LW10 GRN145/740 II DM AL 7035 SP |
| **Full product name** | BGP383 LW10 GRN145/740 II DM AL 7035 SP |
| **Full product code** | 871869634242800 |
| **Order code** | 910925439771 |
| **Material Nr. (12NC)** | 910925439771 |
| **Numerator - Quantity Per Pack** | 1 |
| **EAN/UPC - Product/Case** | 8718696342428 |
| **Numerator - Packs per outer box** | 1 |
| **EAN/UPC - Case** | 8718696342428 |

# Iridium gen3 LED Large

## Dimensional drawing




© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.