



CoreLine Trunking

LL123X 5C6 9

CoreLine Trunking

Whether for a new facility or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Trunking range of LED products can be used to replace general lighting. The process of selecting, installing and maintaining is so easy – it's a simple switch.

Product data

General Information	
Angle	-
Accessory colour	White
Product family code	LL123X [CoreLine Trunking]
ENEC mark	ENEC mark
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Mechanical and Housing	
Overall length	1,730 mm
Overall width	81 mm
Overall height	43 mm
Dimensions (height x width x depth)	43 x 81 x 1730 mm
Material	Steel

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I
Product Data	
Order product name	LL123X 5C6 9
Full product name	LL123X 5C6 9
Full EOC	871829190797800
Order code	90797800
Material no. (12 NC)	910925683072
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8718291907978
Numerator – packs per outer box	1
EAN/UPC – Case	8718291907978

CoreLine Trunking

Dimensional drawing

