



# **High Power GearUnits**

## ECB330 HPI-T1000W 230-240V PA FU

GearUnits, HPI-T High Wattage, 1000 W, 1051 W

Philips is one of the few companies able to provide total floodlight system solutions comprising all necessary elements – floodlight, lamp source and control gear unit. Our innovative high-power GearUnits are designed to meet our customers' need for a compact gear solution that is completely ready for installation. The pre-wired high-power control gear units are intended for use in combination with floodlights that are suitable for high-wattage HID lamps and cannot integrate electrical components because of limited space or high temperatures. A gear unit contains all electrical components (ballast, ignitors, capacitors), wiring and terminal blocks needed to ensure initial lamp ignition and proper operation of the lamp in stabilized current. The electromagnetic high-power GearUnits are available in both IP20 (ECB330) and IP65 (ECP330) versions. Within the GearUnits family there is also an electronic flicker-free ballast version (ECM330) available in IP20, which is suitable for the MVF403 MHN-LA 1000 W and MVF404 MHN-SE HO 2000 W ArenaVision floodlights. The ArenaVision floodlight family is specially designed for TV broadcasts from indoor and outdoor sports facilities. Electronic-ballast GearUnits completely eliminate the flicker effect, thereby guaranteeing perfect images filmed with superslow-motion cameras.

#### **Product data**

General Information	
Lamp family code	HPI-T [HPI-T High Wattage]
Number of gear units	1 unit
Gear	CONV [Conventional]
Product family code	ECB330 [GearUnits]
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-

Value ladder	Performance
Light Technical	
Number of light sources	1
Operating and Electrical	
Input Voltage	230 to 240 V
Line Frequency	50 Hz


Datasheet, 2023, September 19 data subject to change

# **High Power GearUnits**

Power Consumption	1,000 1,051 W
Connection	Screw connection block 3-pole
Temperature	
Ambient temperature range	-30 to +55 ℃
Controls and Dimming	
Dimmable	No
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Energy Efficiency Index	A3

Product Data	
Order product name	ECB330 HPI-T1000W 230-240V PA FU
Full product name	ECB330 HPI-T1000W 230-240V PA FU
Full product code	871829106264600
Order code	910925724812
Material Nr. (12NC)	910925724812
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291062646
Numerator - Packs per outer box	1
EAN/UPC - Case	8718291062646

### Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.