



Malaga SGS101

SGS101 SON-T70W II MR-AS SKD P1 42/60

MALAGA, SON-T, 70 W, Safety class II, Moveable reflector with Allen screw, NEMA socket for photocell, Universal for diameter 42 to 60 mm

Malaga is a versatile road-lighting luminaire. It offers modern styling and quality lighting for safe and comfortable driving, and for area illumination, with low investment and maintenance costs. The optical system has been designed to deliver good beam control and light output. Malaga provides optimal illuminance and good uniformity when the mounting height approximately equals the road width and the mast spacing is approximately 3.5 times the road width. It is suitable for post-top and side-entry mounting; a wall-mounting bracket is also available.

Product data

General Information	
Lamp family code	SON-T [SON-T]
Cap-Base	E27 [E27]
Gear	CONV [Conventional]
Photocell	NEMA socket for photocell
Product family code	SGS101 [MALAGA]
CE mark	Yes
ENEC mark	ENEC mark
Light Technical	
Standard tilt angle posttop	15°
Standard tilt angle side entry	15°
Number of light sources	1
Optical cover type	Polycarbonate bowl/cover

Operating and Electrical Input Voltage 230 V (default) or 240 V Power Consumption 70 W Mechanical and Housing Housing Color Grey Mounting device Universal for diameter 42 to 60 mm Approval and Application Ingress protection code IP43/65 [Wire-protected, rain/spray-proof; dust penetration-protected, jet-proof]		
Input Voltage 230 V (default) or 240 V Power Consumption 70 W Mechanical and Housing Housing Color Grey Mounting device Universal for diameter 42 to 60 mm Approval and Application Ingress protection code IP43/65 [Wire-protected, rain/spray-proof; dust penetration-protected, jet-proof]	Optic type outdoor	Moveable reflector with Allen screw
Input Voltage 230 V (default) or 240 V Power Consumption 70 W Mechanical and Housing Housing Color Grey Mounting device Universal for diameter 42 to 60 mm Approval and Application Ingress protection code IP43/65 [Wire-protected, rain/spray-proof; dust penetration-protected, jet-proof]		
Power Consumption 70 W Mechanical and Housing Housing Color Grey Mounting device Universal for diameter 42 to 60 mm Approval and Application Ingress protection code IP43/65 [Wire-protected, rain/spray-proof; dust penetration-protected, jet-proof]	Operating and Electrical	
Mechanical and Housing Housing Color Grey Mounting device Universal for diameter 42 to 60 mm Approval and Application Ingress protection code IP43/65 [Wire-protected, rain/spray-proof; dust penetration-protected, jet-proof]	Input Voltage	230 V (default) or 240 V
Housing Color Grey Mounting device Universal for diameter 42 to 60 mm Approval and Application Ingress protection code IP43/65 [Wire-protected, rain/spray-proof; dust penetration-protected, jet-proof]	Power Consumption	70 W
Housing Color Grey Mounting device Universal for diameter 42 to 60 mm Approval and Application Ingress protection code IP43/65 [Wire-protected, rain/spray-proof; dust penetration-protected, jet-proof]		
Mounting device Universal for diameter 42 to 60 mm Approval and Application Ingress protection code IP43/65 [Wire-protected, rain/spray-proof; dust penetration-protected, jet-proof]	Mechanical and Housing	
Approval and Application Ingress protection code IP43/65 [Wire-protected, rain/spray-proof; dust penetration-protected, jet-proof]	Housing Color	Grey
Ingress protection code IP43/65 [Wire-protected, rain/spray-proof; dust penetration-protected, jet-proof]	Mounting device	Universal for diameter 42 to 60 mm
Ingress protection code IP43/65 [Wire-protected, rain/spray-proof; dust penetration-protected, jet-proof]		
penetration-protected, jet-proof]	Approval and Application	
	Ingress protection code	IP43/65 [Wire-protected, rain/spray-proof; dust
Mach impact protection ends IVO9 [5 Lyandal protected]		penetration-protected, jet-proof]
ino [5 3 varidat-protected]	Mech. impact protection code	IK08 [5 J vandal-protected]


Datasheet, 2023, September 4 data subject to change


Malaga SGS101


Protection class IEC	Safety class II
Product Data	
Order product name	SGS101 SON-T70W II MR-AS SKD P1 42/60
Full product name	SGS101 SON-T70W II MR-AS SKD P1 42/60
Full product code	872790061407700
Order code	910925812512

Material Nr. (12NC)	910925812512	
Numerator - Quantity Per Pack	1	
EAN/UPC - Product/Case	8727900614077	
Numerator - Packs per outer box 1		
EAN/UPC - Case	8727900614077	

Dimensional drawing









© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.