



# Selenium

## SGP340 SON-T70W K 240V I PC SKD P1 34/42

Selenium LED, SON-T, 70 W, 240 V, Safety class I, Polycarbonate bowl/cover, NEMA socket for photocell, Spigot for diameter 34 to 42 mm

Selenium SGP340 is an efficient, ergonomic road-lighting luminaire. Its simple, rounded form reduces its daytime visual impact, allowing it to integrate into any kind of environment. Selenium incorporates the renowned T-POT reflector for excellent optical performance. Energy savings are possible by means of dimming with a switch or stand-alone Chronosense system (without pilot cable). Selenium is suitable for side-entry or post-top mounting, with a choice of three tilt angles for optimal installation (0, 5, 15<sup>o</sup>).

#### Product data

| General Information            |                           | Optic type outdoor           | Open T-POT                                  |
|--------------------------------|---------------------------|------------------------------|---|
| Lamp family code               | SON-T [SON-T]             |                              |   |
| Cap base                       | E27 [E27]                 | Operating and Electrical     |   |
| Gear                           | CONV [Conventional]       | Input Voltage                | 240 V                                       |
| Photocell                      | NEMA socket for photocell | Power Consumption            | 70 W  |
| Product family code            | BGP340 [Selenium LED]     |                              |   |
| Embedded control               | -                         | Mechanical and Housing       |   |
| CE mark                        | Yes                       | Housing Colour               | Grey  |
| ENEC mark                      | -                         | Mounting device              | Spigot for diameter 34 to 42 mm             |
| Light Technical                |                           | Approval and Application     |   |
| Standard tilt angle post-top   | 5°                        | Ingress protection code      | IP66 [Dust penetration-protected, jet-proof |
| Standard tilt angle side entry | 0°                        | Mech. impact protection code | IK08 [5 J vandal-protected]                 |
| Optical cover type             | Polycarbonate bowl/cover  | Protection class IEC         | Safety class I                              |


### Selenium

| Product | Data |
|---------|------|
|---------|------|

| Order product name   | SGP340 SON-T70W K 240V I PC SKD P1 34/42 |
|----------------------|--|
| Full product name    | SGP340 SON-T70W K 240V I PC SKD P1 34/42 |
| Full EOC             | 871155912702600                          |
| Order code           | 12702600                                 |
| Material no. (12 NC) | 910925838712                             |

| SAP numerator – quantity per pack | 1             |
|-----------------------------------|---------------|
| EAN/UPC - Product/Case            | 8711559127026 |
| Numerator – packs per outer box   | 1             |
| EAN/UPC - Case                    | 8711559127026 |

#### Dimensional drawing



Product

SGP340 SON-T70W K 240V I PC SKD P1 34/42



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 29 - data subject to change