



Selenium

SGP340 SON-T250W K II FG SKD KC 48/60

Selenium LED, SON-T, 250 W, Safety class II, Flat glass, Universal for diameter 48 to 60 mm

Selenium SGP340 is an efficient, ergonomic road-lighting luminaire. Its simple, rounded form reduces its daytime visual impact, allowing it to integrate into any kind of environment. Selenium incorporates the renowned T-POT reflector for excellent optical performance. Energy savings are possible by means of dimming with a switch or stand-alone Chronosense system (without pilot cable). Selenium is suitable for side-entry or post-top mounting, with a choice of three tilt angles for optimal installation (0, 5, 15°).


Product data

General Information		Optic type outdoor	
Lamp family code	SON-T [SON-T]	Open T-POT	
Cap-Base	E40 [E40]	Operating and Electrical	
Gear	CONV [Conventional]	Input Voltage	230 to 240 V
Photocell	-	Power Consumption	250 W
Product family code	BGP340 [Selenium LED]	Mechanical and Housing	
Embedded control	-	Housing Color	Gray
CE mark	Yes	Mounting device	Universal for diameter 48 to 60 mm
ENEC mark	-	Overall height	232 mm
Light Technical		Approval and Application	
Standard tilt angle posttop	5°	Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Standard tilt angle side entry	0°	Mech. impact protection code	IK08 [5 J vandal-protected]
Number of light sources	1	Protection class IEC	Safety class II
Optical cover type	Flat glass		

Product Data	
Order product name	SGP340 SON-T250W K II FG SKD KC 48/60
Full product name	SGP340 SON-T250W K II FG SKD KC 48/60
Full product code	871155912696800
Order code	12696800
Material Nr. (12NC)	910925847412

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711559126968
Numerator - Packs per outer box	1
EAN/UPC - Case	8711559126968

Dimensional drawing



Product
SGP340 SON-T250W K II FG SKD KC 48/60

