



DigiStreet

BGP762 LED210-/740 II DX70 DGR 76

DigiStreet Medium, LED module 21000 lm, 740 neutral white, Safety class II, Distribution extra wide 70, Dark gray, Luminaire surge protection level until 6 kV differential mode and 8 kV common mode, Spigot for diameter 76 mm

Developed with the aim of becoming your long-term partner, the system-ready architecture of DigiStreet enables you to enjoy the benefits of connected lighting systems today and also gets the city ready for the innovations to come! Its two sockets enable you to connect directly to the Philips CityTouch system and it is also prepared to connect you to the future innovations of IoT. Next to this, each individual luminaire is uniquely identifiable, thanks to the Philips Service tag application. With a simple scan of a QR code, placed on the inside of the mast door, you gain instant access to the luminaire configuration, making maintenance and programming operations faster and easier, no matter what stage of the luminaire's lifetime. DigiStreet is also equipped with dedicated light recipes that: 1) maintain optimal ecosystems for bats or 2) preserve a dark night sky.

Product data

| General Information | | |
|--------------------------|---|----------------------------|
| Lamp family code | LED210 [LED module 21000 lm] | |
| Light source replaceable | No | |
| Number of gear units | 1 unit | |
| Gear | EB [Electronic] | |
| Driver included | Yes | |
| Remarks | *-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value. | |
| | | |
| Light source engine type | | LED |
| Product family code | | BGP762 [DigiStreet Medium] |
| Lighting Technology | | LED |
| Value ladder | | Specification |
| CE mark | | Yes |
| Warranty period | | 5 years |
| Flammability mark | | - |

| | |
|-------------------|----------------------------------|
| ENEC mark | ENEC mark |
| Glow-wire test | Temperature 650 °C, duration 5 s |
| EU RoHS compliant | Yes |

Light Technical

| | |
|------------------------------------|----------------------------|
| Upward light output ratio | 0 |
| Luminous Flux | 18,060 lm |
| Standard tilt angle posttop | 0° |
| Standard tilt angle side entry | 0° |
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 143 lm/W |
| Color rendering index (CRI) | 70 |
| Number of light sources | 1 |
| Light source color | 740 neutral white |
| Optical cover type | Flat glass |
| Luminaire light beam spread | 106° x 86° |
| Optic type outdoor | Distribution extra wide 70 |

Operating and Electrical

| | |
|--|-------------------------------|
| Input Voltage | 220-240 V |
| Line Frequency | 50 to 60 Hz |
| Initial CLO power consumption | - W |
| Average CLO power consumption | - W |
| End CLO power consumption | - W |
| Inrush current | 53 A |
| Inrush time | 0.3 ms |
| Power Consumption | 126 W |
| Power Factor (Fraction) | 0.99 |
| Connection | Screw connection block 3-pole |
| Cable | - |
| Number of products on MCB of 16 A type B | 8 |

Temperature

| | |
|---------------------------|---------------|
| Ambient temperature range | -40 to +50 °C |
|---------------------------|---------------|

Controls and Dimming

| | |
|-------------------------------|----------------------------|
| Dimmable | No |
| Driver/power unit/transformer | Power supply unit (On/Off) |
| Control interface | - |
| Constant light output | No |

Mechanical and Housing

| | |
|------------------------|---------------|
| Housing Material | Aluminum |
| Reflector material | Polycarbonate |
| Optic material | Acrylate |
| Optical cover material | Glass |
| Fixation material | Steel |

| | |
|-------------------------------------|---------------------------|
| Housing Color | Dark gray |
| Mounting device | Spigot for diameter 76 mm |
| Optical cover shape | Flat |
| Optical cover finish | Clear |
| Overall length | 860 mm |
| Overall width | 361 mm |
| Overall height | 107 mm |
| Effective projected area | 0.068 m² |
| Dimensions (Height x Width x Depth) | 107 x 361 x 860 mm |

Approval and Application

| | |
|--|--|
| Ingress protection code | IP66 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK09 [10 J] |
| Surge Protection (Common/Differential) | Luminaire surge protection level until 6 kV differential mode and 8 kV common mode |
| Protection class IEC | Safety class II |
| Photobiological risk | Photobiological risk group 0 @200mm to EN62778 |

Initial Performance (IEC Compliant)

| | |
|---------------------------------------|----------------------|
| Luminous flux tolerance | +/-7% |
| Initial chromaticity | (0.38, 0.38) SDCM <5 |
| Power consumption tolerance | +/-10% |
| Init. Color Rendering Index Tolerance | +/-2 |

Over Time Performance (IEC Compliant)

| | |
|--|------|
| Control gear failure rate at median useful life 100000 h | 10 % |
| Lumen maintenance at median useful life* 100000 h | L91 |

Application Conditions

| | |
|------------------------------------|----------------|
| Performance ambient temperature Tq | 25 °C |
| Maximum dim level | Not applicable |

Product Data

| | |
|---------------------------------|-----------------------------------|
| Order product name | BGP762 LED210-/740 II DX70 DGR 76 |
| Full product name | BGP762 LED210-/740 II DX70 DGR 76 |
| Full product code | 871869637837300 |
| Order code | 37837300 |
| Material Nr. (12NC) | 910925863714 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8718696378373 |
| Numerator - Packs per outer box | 1 |
| EAN/UPC - Case | 8718696378373 |

Dimensional drawing

