



# GentleSpace gen2

## BY470P GRN130S/840 PSD NB GC WH

GentleSpace 2, LED GreenLine system flux 13000 lm, 840 neutral white, Power supply unit with DALI interface, Narrow beam, Clear glass, White

With the introduction of the GentleSpace LED luminaire in 2011, Philips achieved a breakthrough in high-bay lighting, offering a huge reduction in power consumption, a long service life and an innovative design. Now, with GentleSpace gen2, Philips is setting a new standard in the market, with an improved total cost of ownership, even in extreme conditions. In addition, a high diversity of options are available to ensure an ideal solution for your application like optics, coatings and enabling the use of a central emergency grid (PSED).

### Product data

General Information		
Lamp family code	GRN130S [LED GreenLine system flux 13000 lm]	useful life (B50) value also represents the B10 value.
Cap base	- [-]	<b>Product family code</b>
Light source replaceable	Yes	BY470P [GentleSpace 2]
Number of gear units	Unit	<b>Lighting Technology</b>
Gear	EB [Electronic]	LED
Driver included	Yes	<b>Embedded control</b>
Remarks	*- According to the Lighting Europe guidance paper 'Evaluating performance of LED based luminaires – January 2018': statistically there is no relevant difference in lumen maintenance between the B50 and, for example, the B10. Therefore, the median	-
		<b>CE mark</b>
		Yes
		<b>Warranty period</b>
		5 years
		<b>Flammability mark</b>
		For mounting on easily flammable surfaces
		<b>ENEC mark</b>
		ENEC mark
		<b>Glow-wire test</b>
		Temperature 850 °C, duration 5 s
		<b>EU RoHS compliant</b>
		Yes
		<b>Light Technical</b>
		<b>Luminous Flux</b>
		13,000 lm
		<b>Correlated Colour Temperature</b>
		4000 K

## GentleSpace gen2

Luminous efficacy (rated) (nom.)	149 lm/W
Colour rendering index (CRI)	≥80
Beam angle of light source	114 degree(s)
Light source colour	840 neutral white
Optic type	Narrow beam
Optical cover type	Clear glass
Luminaire light beam spread	30° x 25°
Unified Glare Rating (CEN)	19

### Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Inrush current	4.8 A
Inrush time	2.3 ms
Power Consumption	87 W
Power Factor (Fraction)	0.9
Connection	External connector
Cable	Cord with plug Wieland/Adels compatible 5-pole
Number of products on MCB of 16 A type B	12

### Temperature

Ambient temperature range	-30 to +45 °C
---------------------------	---------------

### Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Control interface	DALI
Constant light output	No

### Mechanical and Housing

Housing material	Aluminium
Reflector material	-
Optic material	Acrylate
Optical cover/lens material	Glass
Fixation material	Stainless steel
Housing Colour	White
Optical cover/lens finish	Clear
Overall length	450 mm
Overall width	350 mm

Overall height	130 mm
Dimensions (height x width x depth)	130 x 350 x 450 mm

### Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Protection class IEC	Safety class I

### Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7%
Initial chromaticity	(0.38, 0.38) SDCM <3
Power consumption tolerance	+/-11%

### Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50,000 h	5 %
Control gear failure rate at median useful life 100,000 h	10 %
Lumen maintenance at median useful life* 50,000 h	L85
Lumen maintenance at median useful life* 100,000 h	L70

### Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	10%
Suitable for random switching	No

### Product Data

Order product name	BY470P GRN130S/840 PSD NB GC WH
Full product name	BY470P GRN130S/840 PSD NB GC WH
Full EOC	871869632230700
Order code	32230700
Material no. (12 NC)	910930205989
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8718696322307
Numerator – packs per outer box	1
EAN/UPC - Case	8718696322307

## GentleSpace gen2

### Dimensional drawing

