# **PHILIPS** Lighting



# X-tend TPS498 C

## TPS498 C 2xTL-D36W HFE D/I C6

2, MASTER TL-D, 36 W, HF Standard, High-gloss optic double parabolic closed

X-tend surface and suspended-mounted luminaires The Philips X-tend family of surface and suspended-mounted luminaires has the perfect combination of cuttingedge technology, functional brilliance and aesthetic appeal. The secret behind Xtend's superb lighting qualities lies in its optic - based on specially designed 3dimensional curves that offer highly efficient light distribution. X-tend meets most ceiling void restrictions, allowing architects and engineers ultimate design flexibility. TPS498 These range of high-performance luminaires is suitable for TL-D or TL5 fluorescent lamps and a wide range of optics. Optics are supplied with the luminaire on request with a choice of direct, direct/indirect lighting. Optics for asymmetrical lighting can be used in combination with a top mirror for higher performance on request. Straight coupling pieces allow connection of luminaires in a line.There are two different top covers: cover-solid and PC-indirect (D/I version).The luminaire is developed with ease of installation in mind, it can be suspended without removing the optic and lamp during installation.

#### **Product data**

General Information				
Lamp family code	TL-D [MASTER TL-D]			
Gear	HFE [HF Standard]			
Light Technical				
Number of light sources	2			
Light source color	-			
Optic type	High-gloss optic double parabolic closed			

Operating and Electrical					
Power Consumption	36 W				
Cable	-				
Approval and Application					
Ingress protection code	IP20 [Finger-protected]				
Product Data					
Order product name	TPS498 C 2xTL-D36W HFE D/I C6				
Full product name	TPS498 C 2xTL-D36W HFE D/I C6				

### X-tend TPS498 C


Full product code	911400628680
Order code	911400628680
Material Nr. (12NC)	911400628680
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	1

#### Dimensional drawing







Product	А	в	с	D
TPS498 C 2xTL-D36W HFE D/I C6	1,240 mm	1,388 mm	1,260 mm	1,280 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.