



ConTempo 150-250-350

RVP350 SON-T400W IC 220V-60Hz S SP

SON-T, 400 W, Symmetrical

The Contempo floodlight has a registered design that blends well with contemporary outdoor environments. It has a rugged pressure die-casted aluminum housing with corrosion resistant powder coating. Contempo also features an integrated energy saving copper ballast, electronic semi-parallel ignitor and capacitor. The unit has passed rigorous tests for dust and water ingress protection.

Product data

| General Information | |
|--------------------------|---------------------|
| Lamp family code | SON-T [SON-T] |
| Cap-Base | E40 [E40] |
| Gear | CONV [Conventional] |
| | |
| Light Technical | |
| Number of light sources | 1 |
| Optic type outdoor | Symmetrical |
| | |
| Operating and Electrical | |
| Input Voltage | 220 V |
| Line Frequency | 60 Hz |
| Power Consumption | 400 W |
| | |
| Mechanical and Housing | |
| Housing Color | - |
| | |

| Approval and Application | |
|---------------------------------|--|
| Ingress protection code | IP65 [Dust penetration-protected, jet-proof] |
| | |
| Product Data | |
| Order product name | RVP350 SON-T400W IC 220V-60Hz S SP |
| Full product name | RVP350 SON-T400W IC 220V-60Hz S SP |
| Full product code | 911401047880 |
| Order code | 911401047880 |
| Material Nr. (12NC) | 911401047880 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 6923828620776 |
| Numerator - Packs per outer box | 1 |
| EAN/UPC - Case | 6923828620776 |
| | |

Datasheet, 2023, April 29 data subject to change

ConTempo 150-250-350

Dimensional drawing



