ConTempo 150-250-350

RVP350 HPI-T250W 220V-60Hz S

MASTER HPI-T Plus, 250 W, Symmetrical

The Contempo floodlight has a registered design that blends well with contemporary outdoor environments. It has a rugged pressure die-casted aluminum housing with corrosion resistant powder coating. Contempo also features an integrated energy saving copper ballast, electronic semi-parallel ignitor and capacitor. The unit has passed rigorous tests for dust and water ingress protection.

Product data

General Information

Lamp family code	HPI-TP [MASTER HPI-T Plus]
Cap-Base	E40 [E40]
Gear	CONV [Conventional]

Light Technical

Number of light sources	1
Optic type outdoor	Symmetrical

Operating and Electrical

Input Voltage	220 V
Line Frequency	60 Hz
Power Consumption	250 W

Mechanical and Housing

Housing Color	-

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]

Product Data

Order product name	RVP350 HPI-T250W 220V-60Hz S
Full product name	RVP350 HPI-T250W 220V-60Hz S
Full product code	911401049780
Order code	911401049780
Material Nr. (12NC)	911401049780
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6923828620943
Numerator - Packs per outer box	1
EAN/UPC - Case	6923828620943

ConTempo 150-250-350

Dimensional drawing

www.lighting.philips.com

2023, April 29 – data subject to change