PHILIPS

Lighting



Essential SmartBright Slim Batten

BN068C LED3/WW L300

Essential SmartBright Slim Batten, 4 W

A flexible solution for long linear light for ambiant lighting.

Product data

General Information	
Light source replaceable	No
Driver included	Yes
CE mark	-
Flammability mark	-
ENEC mark	-

Light Technical	
Optic type	-
Luminaire light beam spread	110°

Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Power Consumption	4 W
Power Factor (Fraction)	0.5

Temperature	
Ambient temperature range	-20 to +35 °C

Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)

Mechanical and Housing	
Housing Material	Polycarbonate
Optic material	Polycarbonate
Housing Color	White

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%


Application Conditions	
Maximum dim level	Not applicable

Essential SmartBright Slim Batten

Product Data	
Order product name	BN068C LED3/WW L300
Full product name	BN068C LED3/WW L300
Full product code	871016330109999
Order code	30109999
Material Nr. (12NC)	911401504331

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163301099
Numerator - Packs per outer box	24
EAN/UPC - Case	8710163301211

Dimensional drawing



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.