

Essential SmartBright Slim Batten

BN068C LED9/CW L900

Essential SmartBright Slim Batten, 10 W, 6500 K

A flexible solution for long linear light for ambiant lighting.

Product data

General Information	
Light source replaceable	No
Driver included	Yes
CE mark	-
Flammability mark	-
ENEC mark	-

Light Technical	
Correlated Color Temperature (Nom)	6500 K
Optic type	-
Luminaire light beam spread	110°

Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Power Consumption	10 W
Power Factor (Fraction)	0.5

Temperature	
Ambient temperature range	-20 to +35 °C

Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)

Mechanical and Housing	
Housing Material	Polycarbonate
Optic material	Polycarbonate
Housing Color	White

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%


Application Conditions	
Maximum dim level	Not applicable

Essential SmartBright Slim Batten

Product Data	
Full product code	871016330105199
Order product name	BN068C LED9/CW L900
Order code	911401504731
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24

Material Nr. (12NC)	911401504731
Full product name	BN068C LED9/CW L900
EAN/UPC - Case	8710163301174
EAN/UPC - Product/Case	8710163301051

Dimensional drawing



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.