



Essential SmartBright Slim Batten

BN068C LED9/WW L900

Essential SmartBright Slim Batten, 10 W

A flexible solution for long linear light for ambiant lighting.

Product data

General Information		
Light source replaceable	No	
Driver included	Yes	
CE mark	-	
Flammability mark	-	
ENEC mark	-	
Light Technical		
Optic type	-	
Luminaire light beam spread	110°	
Operating and Electrical		
Input Voltage	220-240 V	
Line Frequency	50 to 60 Hz	
Power Consumption	10 W	
Power Factor (Fraction)	0.5	
Temperature		
Ambient temperature range	-20 to +35 °C	

Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Mechanical and Housing	
Housing Material	Polycarbonate
Optic material	Polycarbonate
Housing Color	White
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Application Conditions	
Maximum dim level	Not applicable

Datasheet, 2023, September 4 data subject to change

Essential SmartBright Slim Batten

Product Data	
Full product code	871016330103799
Order product name	BN068C LED9/WW L900
Order code	911401504931
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24

Material Nr. (12NC)	911401504931
Full product name	BN068C LED9/WW L900
EAN/UPC - Case	8710163301150
EAN/UPC - Product/Case	8710163301037

Dimensional drawing



