



# SmartBright Slim Panel

RC091V LED26S/840 PSU W60L60

SmartBright Slim Panel, 80 lm/W, 840 neutral white

SmartBright Slim Panel provides the most affordable LED solution to replace TL troffer. Its slim design (height of luminaire only 10mm) and multiple mounting options cater various applications (including plastic ceiling). As an edge light architecture, SlimBright Slim Panel delivers comfortable light with Excellent uniformity.

## Product data

General Information	
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	-
CE mark	CE mark
ENEC mark	-
Warranty period	1 years
EU RoHS compliant	Yes
Light Technical	
Luminous Flux	2,600 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	80 lm/W
Color rendering index (CRI)	>80
Beam angle of light source	- degree(s)

Light source color	840 neutral white
Optic type	Wide beam
Luminaire light beam spread	120°
Operating and Electrical	
Input Voltage	220/240 V
Line Frequency	50 to 60 Hz
Inrush current	8.1 A
Inrush time	100 ms
Power Consumption	34 W
Power Factor (Fraction)	0.9
Connection	Internal connector
Cable	-
Number of products on MCB of 16 A type B	50

## SmartBright Slim Panel

<b>Temperature</b>	
Ambient temperature range	-10 to +35 °C
<b>Controls and Dimming</b>	
Dimmable	No
Driver/power unit/transformer	-
Control interface	-
Constant light output	No
<b>Mechanical and Housing</b>	
Housing Material	Metal
Reflector material	-
Optic material	Polystyrene
Optical cover material	Polystyrene
Fixation material	Steel
Housing Color	White
Optical cover finish	Opal
Overall length	597 mm
Overall width	597 mm
Overall height	41 mm
Dimensions (Height x Width x Depth)	41 x 597 x 597 mm
<b>Approval and Application</b>	
Ingress protection code	IP20 [Finger-protected]

Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class II
<b>Initial Performance (IEC Compliant)</b>	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.43, 0.40) SDCM>5
Power consumption tolerance	+/-10%
<b>Application Conditions</b>	
Maximum dim level	Not applicable
<b>Product Data</b>	
Order product name	RC091V LED26S/840 PSU W60L60
Full product name	RC091V LED26S/840 PSU W60L60
Full product code	692382862456900
Order code	911401512741
Material Nr. (12NC)	911401512741
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6923828624569
Numerator - Packs per outer box	4
EAN/UPC - Case	6923828624569

### Dimensional drawing

