



GreenUp Highbay

BY550P LED100/CW PSU WB

LED module 10500 lm, Cool white, Power supply unit (On/Off), Wide beam

GreenUp Highbay BY550 is a high efficient and reliable LED highbay for industrial high-ceiling facilities without humid and dusty requirement, designed for both new project and retrofit. This lighting system can deliver up to 88% energy savings with the integrated G2 Acticlume Wireless. It delivers point to point replace up to 400W HID and T5 6x54W higbay with easy installation. There are three beam shapes to choose with good light quality CRI85 and UGR 17. Integrated with G2 Acticlume Wireless, GreenUp BY550 provide connected lighting with daylight , occupancy sensor, and ZigBee wireless communication, will increase your savings by upgrading to an intelligent system and delivering one-stop solution for your Factory, Warehouse, Distribution center, Indoor spot hall, and other high ceiling indoor application.

Product data

General Information	
Lamp family code	LED105 [LED module 10500 lm]
Light source replaceable	No
Number of gear units	1 unit
Gear	-
Driver included	Yes
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	-
CE mark	CE mark
ENEC mark	-

Light Technical	
Correlated Color Temperature (Nom)	6500 K
Color rendering index (CRI)	>85
Light source color	Cool white
Optic type	Wide beam
Optical cover type	Polycarbonate bowl/cover clear
Luminaire light beam spread	90°
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Power Consumption	80 W

GreenUp Highbay

Power Factor (Fraction)	0.9
Connection	Screw connection block 3-pole
Cable	-

Temperature

Ambient temperature range	-20 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	Yes

Mechanical and Housing

Housing Material	Metal-Plastic
Optic material	Polymethyl methacrylate
Housing Color	White

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]

Protection class IEC	Safety class I
----------------------	----------------

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-7.5%
Initial chromaticity	-
Power consumption tolerance	+/-10%

Application Conditions

Maximum dim level	Not applicable
-------------------	----------------

Product Data

Order product name	BY550P LED100/CW PSU WB
Full product name	BY550P LED100/CW PSU WB
Full product code	911401524521
Order code	911401524521
Material Nr. (12NC)	911401524521
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

