

PowerBalance RC600B

RC600B LED40S/840 PSD ACL W30L120

LED module, system flux 4000 lm, 840 neutral white, Power supply unit with DALI interface, ActiLume

When it comes to lighting an office space with LED luminaires, people are willing to invest in sustainability, but only at reasonable cost. At the same time, the system should comply with office lighting norms to ensure a comfortable working environment. PowerBalance is an attractively priced LED luminaire specially developed to meet all office requirements. It consumes significantly less energy while offering longer life of the light source, resulting in lower operational cost compared to traditional luminaires.

Product data

General Information	
Lamp family code	LED40S [LED module, system flux 4000 lm]
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore, the median useful life (B50) value also represents the B10 value.
Embedded control	ActiLume
Flammability mark	For mounting on normally flammable surfaces
Glow-wire test	Temperature 650 °C, duration 5 s

Light Technical	
Light source color	840 neutral white

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz

Controls and Dimming	
Driver/power unit/transformer	Power supply unit with DALI interface

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Protection class IEC	Safety class I


PowerBalance RC600B

Application Conditions	
Performance ambient temperature	25 °C
Tq	

Product Data	
Order product name	RC600B LED40S/840 PSD ACL W30L120
Full product name	RC600B LED40S/840 PSD ACL W30L120

Full product code	911401532601
Order code	911401532601
Material Nr. (12NC)	911401532601
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.