



# GreenUp Highbay

## BY550X LED100/NW ACW2 IS HRO

LED module 10500 lm, Neutral white, High-rack optic

GreenUp Highbay BY550 is a high efficient and reliable LED highbay for industrial high-ceiling facilities without humid and dusty requirement, designed for both new project and retrofit. This lighting system can deliver up to 88% energy savings with the integrated G2 Actimlume Wireless. It delivers point to point replace up to 400W HID and T5 6x54W higbay with easy installation. There are three beam shapes to choose with good light quality CRI85 and UGR 17. Integrated with G2 Actilume Wireless, GreenUp BY550 provide connected lighting with daylight , occupancy sensor, and ZigBee wireless communication, will increase your savings by upgrading to an intelligent system and delivering one-stop solution for your Factory, Warehouse, Distribution center, Indoor spot hall, and other high ceiling indoor application.

### Product data

| General Information      |                                   |                                    |                                |
|--------------------------|-----------------------------------|------------------------------------|--------------------------------|
| Lamp family code         | LED105 [LED module 10500 lm]      | Correlated Color Temperature (Nom) | 4000 K                         |
| Light source replaceable | No                                | Luminous Efficacy (rated) (Nom)    | 100 lm/W                       |
| Number of gear units     | 1 unit                            | Color rendering index (CRI)        | >85                            |
| Gear                     | -                                 | Light source color                 | Neutral white                  |
| Driver included          | Yes                               | Optic type                         | High-rack optic                |
| Light source engine type | LED                               | Optical cover type                 | Polycarbonate bowl/cover clear |
| Glow-wire test           | Temperature 650 °C, duration 30 s | Luminaire light beam spread        | 90°                            |
| Flammability mark        | -                                 | Operating and Electrical           |                                |
| CE mark                  | CE mark                           | Input Voltage                      | 220 to 240 V                   |
| ENEC mark                | -                                 | Line Frequency                     | 50 to 60 Hz                    |
| Light Technical          |                                   | Power Consumption                  | 80 W                           |
| Luminous Flux            | 14,000 lm                         | Power Factor (Fraction)            | 0.9                            |
|                          |                                   | Connection                         | Screw connection block 3-pole  |

## GreenUp Highbay

|  |    |
|--|----|
| Cable                                    | -  |
| Number of products on MCB of 16 A type B | 12 |

### Temperature

|                           |               |
|---------------------------|---------------|
| Ambient temperature range | -20 to +40 °C |
|---------------------------|---------------|

### Controls and Dimming

|                               |                                       |
|-------------------------------|---------------------------------------|
| Dimmable                      | Yes                                   |
| Driver/power unit/transformer | Power supply unit with DALI interface |
| Control interface             | -                                     |
| Constant light output         | Yes                                   |

### Mechanical and Housing

|                        |                         |
|------------------------|-------------------------|
| Housing Material       | Metal – Plastic         |
| Optic material         | Polymethyl methacrylate |
| Optical cover material | Polymethyl methacrylate |
| Housing Color          | White                   |
| Optical cover finish   | Clear                   |

### Approval and Application

|                         |                         |
|-------------------------|-------------------------|
| Ingress protection code | IP20 [Finger-protected] |
|-------------------------|-------------------------|

|                              |                |
|------------------------------|----------------|
| Mech. impact protection code | IK03 [0.3 J]   |
| Protection class IEC         | Safety class I |

### Initial Performance (IEC Compliant)

|                             |         |
|-----------------------------|---------|
| Luminous flux tolerance     | +/-7.5% |
| Initial chromaticity        | -       |
| Power consumption tolerance | +/-10%  |

### Application Conditions

|                   |                             |
|-------------------|-----------------------------|
| Maximum dim level | 1% (depends on dimmer, ELV) |
|-------------------|-----------------------------|

### Product Data

|                                 |                              |
|---------------------------------|------------------------------|
| Order product name              | BY550X LED100/NW ACW2 IS HRO |
| Full product name               | BY550X LED100/NW ACW2 IS HRO |
| Full product code               | 911401538621                 |
| Order code                      | 911401538621                 |
| Material Nr. (12NC)             | 911401538621                 |
| Numerator - Quantity Per Pack   | 1                            |
| Numerator - Packs per outer box | 1                            |

## Dimensional drawing

